

NETGEAR GS108T Managed L2 Gigabit Ethernet (10/100/1000) Grey



Model: GS108T-300PES

Manufacturer: NETGEAR

EAN: 606449138634

Product Code: 1250057

R2,277

Certification: CE, FCC, VCCI Class B, C-Tick | Product colour: Grey | AC input frequency: 50 - 60 Hz | Package height: 64 mm | Copper ethernet cabling technology: 100BASE-TX | Copper ethernet cabling technology: 1000BASE-TX | Operating relative humidity (H-H): 0 - 95% | Manual: Yes | Depth: 101 mm | Package width: 226 mm | Package weight: 780 g | Firmware upgradeable: Yes | Height: 27 mm | Products per master (outer) case: 6 pc(s) | Width: 158 mm | Power over Ethernet (PoE): No | Flash memory: 32 MB | Package type: Box | Copper ethernet cabling technology: 10BASE-T | Supported network protocols: HTTP, HTTPS | Networking standards: IEEE 802.3x | MAC address filtering: Yes | Security algorithms: 802.1x RADIUS | Networking standards: IEEE 802.3af | Networking standards: IEEE 802.3az | Processor frequency: 500 MHz | Networking standards: IEEE 802.3at | Storage relative humidity (H-H): 0 - 95% | Power consumption (max): 5.5 W | Networking standards: IEEE 802.3ad | Storage temperature (T-T): -20 - 70 °C | Quality of Service (QoS) support: Yes | Internal memory: 128

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

MB | LED indicators: LAN | AC input voltage: 100 - 240 V | LED indicators: Link | LED indicators: Power | Operating altitude: 0 - 3000 m | Input current: 1.25 A | LED indicators: PoE | LED indicators: Activity | Operating temperature (T-T): 0 - 40 °C | Weight: 430 g | Package depth: 270 mm | LED indicators: Speed | DHCP features: DHCP client | Power connector: DC-in jack | Number of VLANs: 64 | Switching capacity: 16 Gbit/s | IGMP snooping: Yes | Master (outer) case gross weight: 5.49 kg | Master (outer) case width: 214 mm | MAC address table: 8000 entries | Packet buffer memory: 0.5 MB | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Harmonized System (HS) code: 85176990 | Jumbo frames support: Yes | Mean time between failures (MTBF): 2388657 h | Power supply included: Yes | Basic switching RJ-45 Ethernet ports quantity: 8 | Master (outer) case length: 474 mm | Non-operating altitude: 0 - 3000 m | Memory type: RAM | Full duplex: Yes | Master (outer) case height: 312 mm | Store-and-forward: Yes | Link aggregation: Yes | Spanning tree protocol: Yes | Broadcast storm control: Yes | Access Control List (ACL): Yes | Switching protocols: SNMP | Rate limiting: Yes | DC input voltage: 54 V | Switch layer: L2 | Warnings: Make sure the ventilation of the equipment is not blocked. | Switch type: Managed | Number of multicast groups filtered: 256 | Management protocols: SNMP | Data link protocols: Ethernet, Fast Ethernet, Gigabit Ethernet | Heat dissipation: 18.66 BTU/h | Warnings: Avoid contact of the device with liquid. | IPv4 multicast entries: 32 | Warnings: Follow the safety guidelines for electrical current. | Flow control support: Yes | Multicast support: Yes | Access Control List (ACL) IPv6 entries: 100 | Stackable: No | Port mirroring: Yes | MAC address auto-learning supported: Yes

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950