

**NETGEAR
GS110TP
Managed
L2/L3/L4 Gigabit
Ethernet
(10/100/1000)
Power over
Ethernet (PoE)
Grey**



Model: GS110TP-300EUS

Manufacturer: NETGEAR

EAN: 606449137644

Product Code: 1250058

R3,877

Certification: CE, FCC, VCCI Class B, C-Tick | AC input voltage: 100 - 240 V | LED indicators: Link |
Number of VLANs: 64 | Heat dissipation: 237.38 BTU/h | Switch type: Managed | Flow control support:
Yes | Web-based management: Yes | MAC address filtering: Yes | Networking standards: IEEE 802.3u
| Spanning tree protocol: Yes | Processor frequency: 500 MHz | Networking standards: IEEE 802.3af |
Input current: 1.25 A | Package type: Box | LED indicators: LAN | Mean time between failures (MTBF):
1200041 h | LED indicators: Speed | Store-and-forward: Yes | Operating altitude: 0 - 3000 m |

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

Products per master (outer) case: 6 pc(s) | LED indicators: Power | Broadcast storm control: Yes | Link aggregation: Yes | LED indicators: Activity | Access Control List (ACL): Yes | Quality of Service (QoS) support: Yes | Operating temperature (T-T): 0 - 40 °C | Product colour: Grey | Storage temperature (T-T): -20 - 70 °C | Master (outer) case width: 274 mm | Power consumption (max): 15.1 W | Switching capacity: 20 Gbit/s | Power over Ethernet plus (PoE+) ports quantity: 8 | Copper ethernet cabling technology: 10BASE-T | Networking standards: IEEE 802.3ab | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Total Power over Ethernet (PoE) budget: 69.5 W | Package width: 161 mm | DHCP features: DHCP client | Internal memory: 128 MB | Flash memory: 32 MB | Copper ethernet cabling technology: 1000BASE-T | MAC address auto-learning supported: Yes | Manual: Yes | Master (outer) case gross weight: 9.73 kg | Operating relative humidity (H-H): 0 - 95% | Rate limiting: Yes | IPv4 multicast entries: 32 | Data link protocols: Ethernet, Fast Ethernet, Gigabit Ethernet | Networking standards: IEEE 802.3x | Switch layer: L2/L3/L4 | LED indicators: PoE | Copper ethernet cabling technology: 100BASE-TX | Height: 27 mm | DC input voltage: 54 V | IGMP snooping: Yes | Harmonized System (HS) code: 85176990 | Width: 236 mm | Rack mounting: No | ARP inspection: Yes | AC input frequency: 50 - 60 Hz | Access Control List (ACL) IPv6 entries: 100 | Networking standards: IEEE 802.3i | Basic switching RJ-45 Ethernet ports quantity: 8 | Security algorithms: 802.1x RADIUS | Multicast support: Yes | Full duplex: Yes | Package depth: 267 mm | Jumbo frames support: Yes | Package height: 86 mm | Number of multicast groups filtered: 256 | Power over Ethernet (PoE): Yes | Networking standards: IEEE 802.3z | Power supply included: Yes | Switching protocols: SNMP | Storage relative humidity (H-H): 0 - 95% | Depth: 101 mm | Power over Ethernet (PoE) power per port: 55 W | Port mirroring: Yes | Package weight: 1.49 kg | Memory type: RAM | Weight: 610 g | Packet buffer memory: 0.5 MB | MAC address table: 8000 entries | Supported network protocols: HTTP, HTTPS | Master (outer) case length: 350 mm | Master (outer) case height: 309 mm | Non-operating altitude: 0 - 3000 m | Management protocols: SNMP | SFP module slots quantity: 2

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950