

NETGEAR 52- Port PoE Gigabit/10G Stackable Smart Switch (GS752TXP)



Model: GS752TXP-300EUS

Manufacturer: NETGEAR

EAN: 606449171181

Product Code: 1250060

R17,358

Storage relative humidity (H-H): 0 - 95% | Power over Ethernet (PoE): Yes | Networking standards: IEEE 802.1w | Networking standards: IEEE 802.3ad | Networking standards: IEEE 802.1ab | Networking standards: IEEE 802.1D | Basic switching RJ-45 Ethernet ports type: 10G Ethernet (100/1000/10000) | MAC address filtering: Yes | Networking standards: IEEE 802.3 | Networking standards: IEEE 802.3ab | Networking standards: IEEE 802.1as | Networking standards: IEEE 802.3i | Networking standards: IEEE 802.1Q | Networking standards: IEEE 802.3x | Networking standards: IEEE 802.1s | Networking standards: IEEE 802.1x | Power over Ethernet plus (PoE+) ports quantity: 48 | Networking standards: IEEE 802.3u | Packet buffer memory: 16 MB | Basic switching RJ-45 Ethernet ports quantity: 48 | MAC address table: 16000 entries | VLAN support: Yes | Warnings: Follow the safety guidelines for electrical current. | DHCP features: DHCP client | Power consumption (max): 51 W | Flash memory: 64 MB | Warnings: Make sure the ventilation of the equipment is not

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

blocked. | Weight: 5.54 kg | Broadcast storm control: Yes | Link aggregation: Yes | Latency (10 Gbps): 4.107 μ s | Switch layer: L2/L3/L4 | Port mirroring: Yes | Spanning tree protocol: Yes | Power source: AC | Rate limiting: Yes | Stackable: Yes | Virtual LAN features: Voice VLAN | Depth: 345 mm | Warnings: Avoid contact of the device with liquid. | Flow control support: Yes | Rack mounting: Yes | Operating altitude: 0 - 3000 m | Mean time between failures (MTBF): 1296949 h | Width: 440 mm | Number of static routes: 32 | Full duplex: Yes | Built-in processor: Yes | SFP+ module slots quantity: 4 | Access Control List (ACL): Yes | 10G support: Yes | Product colour: Black | Heat dissipation: 2944.6 BTU/h | Switch type: Managed | IGMP snooping: Yes | SSH/SSL support: Yes | Noise level: 36.6 dB | Storage temperature (T-T): -20 - 70 °C | Total Power over Ethernet (PoE) budget: 380 W | Operating temperature (T-T): 0 - 50 °C | Height: 43 mm | Operating relative humidity (H-H): 0 - 95% | Power supply included: Yes | Static route: Yes | Non-operating altitude: 0 - 3000 m

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950