

# **NETGEAR 8x1G PoE+ 110W 1x1G and 1xSFP Managed Switch**



Model: GSM4210PD-100EUS

Manufacturer: NETGEAR

EAN: 606449160192

Product Code: 1250061

## **R16,649**

Warnings: Avoid contact of the device with liquid. | Warnings: Follow the safety guidelines for electrical current. | Warnings: Make sure the ventilation of the equipment is not blocked. | Depth: 140 mm | Processor model: ARM Cortex-A9 | IGMP snooping: Yes | AC input frequency: 50 - 60 Hz | Operating relative humidity (H-H): 0 - 90% | Authentication type: RADIUS | Rack mounting: Yes | Multicast support: Yes | IPv4 multicast entries: 2000 | MAC address table: 16000 entries | Power source: AC/DC | Width: 210 mm | Power supply included: Yes | DHCP features: DHCPv6 server | DHCP features: DHCPv6 relay | DHCP features: DHCP Option 82 | Switch layer: L2/L3 | LED indicators: PoE | Power over Ethernet (PoE): Yes | DHCP features: DHCP snooping | Networking standards: IEEE 802.3ad | Networking standards: IEEE 802.1s | LED indicators: Status | Internal memory: 2048 MB | Rate limiting: Yes | Height: 40 mm | User guide: Yes | SSH/SSL support: Yes | LED indicators: Power | Heat dissipation: 559.555 BTU/h | Networking standards: IEEE 802.3at | DHCP features: DHCPv6 client | Networking standards: IEEE 802.1x | Networking standards: IEEE 802.3bt | Operating altitude: 0 - 3000 m | Networking standards: IEEE 802.3af | Built-in processor: Yes | Manual: Yes | Processor frequency: 1250 MHz | DHCP features: DHCP server | Full duplex: Yes | BPDU filtering/protection: Yes

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

| Networking standards: IEEE 802.1Q | Networking standards: IEEE 802.3x | DHCP features: DHCP relay | Store-and-forward: Yes | Networking standards: IEEE 802.1D | Networking standards: IEEE 802.1ab | Power over Ethernet (PoE) power per port: 30 W | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Spanning tree protocol: Yes | Storage relative humidity (H-H): 0 - 95% | Total Power over Ethernet (PoE) budget: 110 W | Networking standards: IEEE 802.1w | AC input voltage: 220 - 240 V | Access Control List (ACL): Yes | Loop protection: Yes | Product colour: Black | Authentication: MAC-based authentication | Switching capacity: 24 Gbit/s | Weight: 967 g | Power over Ethernet plus (PoE+) ports quantity: 8 | DHCP features: DHCPv6 snooping | Noise level: 30.06 dB | Non-operating altitude: 0 - 3000 m | Basic switching RJ-45 Ethernet ports quantity: 8 | Link aggregation: Yes | Quality of Service (QoS) support: Yes | Switch type: Managed | Storage temperature (T-T): -20 - 70 °C | Operating temperature (T-T): 0 - 50 °C | Broadcast storm control: Yes

---

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950