

Ubiquiti Pro Max 48 L3 2.5G Ethernet (100/1000/2500) 1U Grey



Model: USW-Pro-Max-48

Manufacturer: UBIQUITI

EAN: 810084692745

Product Code: 1250078

R15,866

SFP+ module slots quantity: 4 | Operating relative humidity (H-H): 10 - 90% | Width: 442.4 mm | Switch layer: L3 | Switching capacity: 224 Gbit/s | Weight: 4.8 kg | Product colour: Grey | Rack mounting: Yes | Operating temperature (T-T): -5 - 40 °C | Static route: Yes | Power consumption (max): 100 W | Height: 43.7 mm | Compliance certificates: Federal Communications Commission (FCC) | Forwarding rate: 166.656 Mpps | IGMP snooping: Yes | DHCP features: DHCP relay | Compliance certificates: Industry Canada (IC) | AC input voltage: 100 - 240 V | LED indicators: Link | Reset button: Yes | Broadcast storm control: Yes | Loop protection: Yes | Rate limiting: Yes | Power source: AC/DC | Networking standards: IEEE 802.1x | Form factor: 1U | Stackable: Yes | DHCP features: DHCP snooping | Throughput: 112 Gbit/s | Power supply included: Yes | Power over Ethernet (PoE): No | Cables included: Power | LED indicators: Status | VLAN support: Yes | Warnings: Follow the safety guidelines for electrical current. | Gigabit Ethernet (copper) ports quantity: 32 | Basic switching RJ-45 Ethernet ports quantity: 48 | 10G support: Yes | Port mirroring: Yes | AC input

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

frequency: 50/60 Hz | Redundant power supply (RPS) support: Yes | Housing material: SGCC | Compliance certificates: CE | Display type: LCM | Flow control support: Yes | Jumbo frames support: Yes | Depth: 325 mm | Virtual LAN features: Voice VLAN | Mounting brackets included: Yes | LED indicators: Network | LED indicators: Speed | Power connector: AC/DC | Warnings: Make sure the ventilation of the equipment is not blocked. | Warnings: Avoid contact of the device with liquid. | Basic switching RJ-45 Ethernet ports type: 2.5G Ethernet (100/1000/2500) | 2.5G Ethernet (copper) ports quantity: 16

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950