

Ubiquiti Pro Max 16 L3 2.5G Ethernet (100/1000/2500) 1U Grey



Model: USW-Pro-Max-16

Manufacturer: UBIQUITI

EAN: 810084694565

Product Code: 1250095

R7,210

Form factor: 1U | Weight: 1.95 kg | LED indicators: Link | Reset button: Yes | Power over Ethernet (PoE): No | LED indicators: Status | LED indicators: Network | Input current: 5 A | Input voltage: 4.8 - 5.2 V | Operating relative humidity (H-H): 10 - 90% | Product colour: Grey | Quality of Service (QoS) support: Yes | Operating temperature (T-T): -5 - 40 °C | LED indicators: Speed | Networking standards: IEEE 802.1x | DHCP features: DHCP relay | Power supply included: Yes | Switch layer: L3 | DHCP features: DHCP snooping | Throughput: 42 Gbit/s | Height: 43.7 mm | Cables included: Power | Fanless: Yes | Flow control support: Yes | DHCP features: DHCP server | Power connector: AC/DC | Display type: LCM | Width: 325.1 mm | Rack mounting: Yes | Static route: Yes | Basic switching RJ-45 Ethernet ports type: 2.5G Ethernet (100/1000/2500) | Redundant power supply (RPS) support: Yes | Housing material: SGCC | Authentication type: IEEE 802.1x | IGMP snooping: Yes | Number of VLANs: 1000 | Rack mount kit: Yes | MAC address table: 16000 entries | Broadcast storm control: Yes | Gigabit Ethernet (copper) ports quantity: 12 | Jumbo frames support: Yes | Virtual LAN features:

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

Voice VLAN | Power consumption (max): 25 W | 10G support: Yes | Depth: 160 mm | Forwarding rate: 62 Mpps | Switching capacity: 84 Gbit/s | Port mirroring: Yes | Packet buffer memory: 1.5 MB | Basic switching RJ-45 Ethernet ports quantity: 16 | DHCP features: DHCP guarding | Link aggregation: Yes | Stackable: Yes | Rate limiting: Yes | VLAN support: Yes | IPv4 routes: 512 | 2.5G Ethernet (copper) ports quantity: 4 | Compliance certificates: Industry Canada (IC) | Warnings: Follow the safety guidelines for electrical current. | Loop protection: Yes | Warnings: Make sure the ventilation of the equipment is not blocked. | SFP+ module slots quantity: 2 | Compliance certificates: National Defense Authorization Act (NDAA) | Warnings: Avoid contact of the device with liquid. | Compliance certificates: Federal Communications Commission (FCC) | Compliance certificates: CE | Heat dissipation: 85.3 BTU/h | Access Control List (ACL): Yes

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950