

**Ubiquiti USW-
PRO-MAX-48-
POE network
switch L3 2.5G
Ethernet
(100/1000/2500)
Power over
Ethernet (PoE)
Grey**



Model: USW-Pro-Max-48-PoE

Manufacturer: UBIQUITI

EAN: 810084692721

Product Code: 1250097

R30,107

Power consumption (max): 820 W | Quality of Service (QoS) support: Yes | Cables included: Power | Depth: 399.6 mm | Power source: AC | Rack mounting: Yes | Weight: 6.2 kg | Power over Ethernet (PoE): Yes | Width: 442.4 mm | Display type: LCM | Manual: Yes | AC input frequency: 50/60 Hz | Operating relative humidity (H-H): 10 - 90% | Form factor: 1U | Reset button: Yes | Networking standards: IEEE 802.1x | Height: 43.7 mm | Redundant power supply (RPS) support: Yes | Housing material: SGCC | Operating temperature (T-T): -5 - 40 °C | Total Power over Ethernet (PoE) budget:

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

720 W | Product colour: Grey | AC input voltage: 100 - 240 V | LED indicators: System | VLAN support: Yes | 2.5G Ethernet (copper) ports quantity: 16 | DHCP features: DHCP server | IGMP snooping: Yes | DHCP features: DHCP relay | DHCP features: DHCPv6 snooping | Switch layer: L3 | Number of VLANs: 1000 | Rack mount kit: Yes | Virtual LAN features: Voice VLAN | Jumbo frames support: Yes | Rate limiting: Yes | MAC address table: 32000 entries | Packet buffer memory: 2 MB | Basic switching RJ-45 Ethernet ports quantity: 48 | Heat dissipation: 341.2 BTU/h | Switching capacity: 224 Gbit/s | Power supply included: Yes | Sustainability compliance: Yes | Power over Ethernet plus (PoE+) ports quantity: 32 | Backlight display: Yes | Throughput: 112 Gbit/s | Switch type: Managed | DHCP features: DHCP guarding | Power over Ethernet (PoE) type supported: PoE+ | Power over Ethernet (PoE) voltage: 57 V | SFP+ module slots quantity: 4 | Power over Ethernet (PoE) type supported: PoE++ (4PPoE) | Static route: Yes | Gigabit Ethernet (copper) ports quantity: 32 | Broadcast storm control: Yes | Loop protection: Yes | Flow control support: Yes | IPv4 routes: 12000 | 10G support: No | Forwarding rate: 167 Mpps | Power connector: AC-in jack | Port mirroring: Yes | Power over Ethernet (PoE) power per port: 15.4 W | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Warnings: Follow the safety guidelines for electrical current. | Power over Ethernet 4PPoE (PoE++) ports quantity: 16 | Warnings: Make sure the ventilation of the equipment is not blocked. | Compliance certificates: National Defense Authorization Act (NDAA) | Compliance certificates: Industry Canada (IC) | Compliance certificates: CE | Compliance certificates: Federal Communications Commission (FCC) | Warnings: Avoid contact of the device with liquid.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950