

Ubiquiti UniFi Flex Mini 2.5G Managed 2.5G Ethernet (100/1000/2500) Power over Ethernet (PoE) Desktop White



Model: USW-Flex-2.5G-5

Manufacturer: UBIQUITI

EAN: 810084696040

Product Code: 1250098

R1,814

Minimum system requirements: UniFi Network Version 8.4.62 and later | Certification: CE, FCC, IC | Form factor: Desktop | Weight: 206 g | Power consumption (max): 5 W | Reset button: Yes | LED indicators: Power | LED indicators: Activity | Input current: 1 A | Operating temperature (T-T): -20 - 45 °C | LED indicators: Progress | Product colour: White | AC adapter included: Yes | Operating relative humidity (H-H): 10 - 90% | Power over Ethernet (PoE): Yes | Power source: AC/DC/PoE | Networking features: STP / RSTP with priorities and port-level disable, Egress rate limit | Compliance certificates: Industry Canada (IC) | Compliance certificates: CE | Compliance certificates: Federal Communications Commission (FCC) | Warnings: Follow the safety guidelines for electrical current. | Warnings: Make

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

sure the ventilation of the equipment is not blocked. | Warnings: Avoid contact of the device with liquid. | 2.5G Ethernet (copper) ports quantity: 5 | Multicast support: Yes | Depth: 90 mm | Width: 117.1 mm | USB Type-C ports quantity: 1 | 10G support: No | Rate limiting: Yes | Jumbo frames support: Yes | Switching capacity: 25 Gbit/s | Copper ethernet cabling technology: 2.5GBASE-T | Power plug type: Type A | Forwarding rate: 18.6 Mpps | Basic switching RJ-45 Ethernet ports quantity: 5 | Flow control support: Yes | Broadcast storm control: Yes | DC input voltage: 5 V | Housing material: Polycarbonate (PC) | Basic switching RJ-45 Ethernet ports type: 2.5G Ethernet (100/1000/2500) | Switch type: Managed | Height: 21.2 mm | Port mirroring: Yes | Throughput: 12.5 Gbit/s | Power connector: USB | Power supply included: Yes | Power over Ethernet (PoE) voltage: 57 V | Power over Ethernet (PoE) power per port: 6.4 W

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950