

**Ubiquiti UniFi
Pro XG 24 PoE
Managed L2/L3
10G Ethernet
(100/1000/10000)
Power over
Ethernet (PoE)
1U Grey**



Model: USW-Pro-XG-24-PoE

Manufacturer: UBIQUITI

EAN: 810177160762

Product Code: 1250102

R41,775

Width: 442 mm | Rack mounting: Yes | Quality of Service (QoS) support: Yes | IGMP snooping: Yes | Power over Ethernet (PoE): Yes | Stackable: Yes | Depth: 480 mm | Display type: LCM | Static route: Yes | Power supply included: Yes | Loop protection: Yes | Broadcast storm control: Yes | Switching capacity: 460 Gbit/s | Weight: 7.9 kg | Power source: AC/DC | Rate limiting: Yes | Multicast support: Yes | Virtual LAN features: Interface-based VLAN | MAC address table: 128000 entries | Virtual LAN features: Voice VLAN | Switch type: Managed | Power consumption (max): 870 W | Port mirroring: Yes | Switch layer: L2/L3 | Reset button: Yes | VLAN support: Yes | Throughput: 230 Gbit/s | Cables included: Power | Flow control support: Yes | 10G support: Yes | Height: 44 mm | Rack mount kit: Yes

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

| Access Control List (ACL) IPv4 entries: 256 | Product colour: Grey | SFP28 ports quantity: 2 | Basic switching RJ-45 Ethernet ports quantity: 24 | Form factor: 1U | Jumbo frames support: Yes | DHCP features: DHCPv6 snooping | AC input voltage: 100 - 240 V | Power over Ethernet (PoE) type supported: PoE+++ | DHCP features: DHCP guarding | DHCP features: DHCP server | Operating relative humidity (H-H): 10 - 90% | Forwarding rate: 342 Mpps | Power connector: AC/DC | 10G Ethernet (copper) ports quantity: 16 | AC input frequency: 50/60 Hz | Number of VLANs: 1000 | DHCP features: DHCP relay | Packet buffer memory: 8 MB | Backlight display: Yes | IPv4 routes: 256000 | Operating temperature (T-T): -5 - 40 °C | Redundant power supply (RPS) support: Yes | Housing material: SGCC | Basic switching RJ-45 Ethernet ports type: 10G Ethernet (100/1000/10000) | 2.5G Ethernet (copper) ports quantity: 8 | Total Power over Ethernet (PoE) budget: 720 W | Power over Ethernet (PoE) power per port: 15.4 W | Power over Ethernet 4PPoE (PoE++) ports quantity: 24 | Compliance certificates: Federal Communications Commission (FCC) | Compliance certificates: CE | Compliance certificates: Industry Canada (IC) | Compliance certificates: National Defense Authorization Act (NDAA)

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950