

Digitus 2D Barcode Hand Scanner, QR- Code Compatible



Model: DA-81002

Manufacturer: DIGITUS

EAN: 4016032473640

Product Code: 1250357

R1,159

Compatible operating systems: Mac/Linux | Package width: 200 mm | Package height: 80 mm | International Protection (IP) code: IP54 | Depth: 87 mm | Harmonized System (HS) code: 84716070 | Width: 63 mm | Scanner type: 1D/2D | Sensor type: CMOS | Linear (1D) barcodes supported: Codabar | Linear (1D) barcodes supported: GS1-128 (UCC/EAN-128) | Linear (1D) barcodes supported: EAN-13 | Linear (1D) barcodes supported: EAN-8 | Input voltage: 5 V | Linear (1D) barcodes supported: ITF-6 | Linear (1D) barcodes supported: Code 32 | Linear (1D) barcodes supported: Code 39 | Height: 165 mm | Windows operating systems supported: Yes | Tilt reading angle: -60 - 60° | Package depth: 140 mm | Linear (1D) barcodes supported: GS1 DataBar | Linear (1D) barcodes supported: IATA | Linear (1D) barcodes supported: ITF-14 | Linear (1D) barcodes supported: ISSN | Linear (1D) barcodes supported: Code 128 | Linear (1D) barcodes supported: EAN 128 | Read rate (max): 200 reads/s | Linear (1D) barcodes supported: MSI | Linear (1D) barcodes supported: Code 93 | Linear (1D) barcodes supported: U.P.C. | Linear (1D) barcodes supported: Industrial 2 of 5 | Light source: 650 nm

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

| Standard interfaces: RJ-45, USB | Maximum scan width: 10 cm | Power consumption: 120 mA |
Mobile operating systems supported: Android | Mobile operating systems supported: iOS | Housing
material: Acrylonitrile butadiene styrene (ABS) | 2D (matrix & stacked) barcodes supported: QR Code
| Housing material: Polycarbonate (PC) | Connectivity technology: Wired | Operating temperature (T-
T): -20 - 50 °C | Power source type: USB | Country of origin: China | 2D (matrix & stacked) barcodes
supported: PDF417 | Package weight: 1.06 kg | 2D (matrix & stacked) barcodes supported: Data
Matrix | Weight: 120 g | Product colour: Black | Warnings: Avoid direct contact with eyes. | Cable
length: 2 m | Storage temperature (T-T): -40 - 70 °C | Type: Handheld bar code reader | Warnings:
Store away from sources of moisture. | Warnings: The appliance should be disposed of in accordance
with local electro-waste regulations. | UK Trade Tariff code: 84719000

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices
may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or
typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950