

Zebra DS9308-SR Fixed bar code reader 1D/2D LED Black



Model: DS9308-SR4U2100AZE

Manufacturer: ZEBRA

EAN:

Product Code: 1250362

R3,227

Certification: EN 50581:2012, RoHS 2011/65/EU (2015/863) - EN 50581:2012, IEC 63000, REACH 1907/2006, IEC 62368-1 2nd ed. EN 62368-1:2014/AC:2015, UL/IEC 60950-1, 2nd ed. CAN/CSA C22.2 No.60950-1, 2nd ed. IEC 62471:2006 (Ed.1.0), EN 62471:2008 (LED), FCC 47 CFR Part 15B, ICES-003, EN55032, EN55024, EN55035, VCCI, and SABS | Warnings: Avoid direct contact with eyes. |

Warnings: Store away from sources of moisture. | Warnings: The appliance should be disposed of in accordance with local electro-waste regulations. | Linear (1D) barcodes supported: Code 128 |

Operating relative humidity (H-H): 5 - 95% | Linear (1D) barcodes supported: Code 11 | Linear (1D)

barcodes supported: EAN-13 | Depth: 83 mm | Scanner type: 1D/2D | Height: 145 mm | Linear (1D)

barcodes supported: Codabar | Linear (1D) barcodes supported: Code 93 | Linear (1D) barcodes

supported: U.P.C. | Linear (1D) barcodes supported: Code 39 | Weight: 318 g | Sensor type: LED |

Pitch reading angle: -60 - 60° | Linear (1D) barcodes supported: MSI | Linear (1D) barcodes

supported: GS1 DataBar | Working distance: 66 cm | Product colour: Black | Light levels (direct

sunlight): 0 - 107700 lx | Connectivity technology: Wired | International Protection (IP) code: IP52 |

Storage temperature (T-T): -40 - 70 °C | Optical sensor resolution (W x H): 1280 x 800 pixels |

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices

may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or

typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

Operating temperature (T-T): 0 - 50 °C | Standard interfaces: RS-232, USB | Harmonized System (HS) code: 84716070 | Width: 86 mm | Input voltage: 5.5 V | 2D (matrix & stacked) barcodes supported: Data Matrix | 2D (matrix & stacked) barcodes supported: MaxiCode | 2D (matrix & stacked) barcodes supported: TLC-39 | 2D (matrix & stacked) barcodes supported: Composite Codes | 2D (matrix & stacked) barcodes supported: QR Code | 2D (matrix & stacked) barcodes supported: Micro QR Code | Type: Fixed bar code reader | 2D (matrix & stacked) barcodes supported: Han Xin | 2D (matrix & stacked) barcodes supported: PDF417 | Power source type: USB | 2D (matrix & stacked) barcodes supported: Aztec Code | 2D (matrix & stacked) barcodes supported: MicroPDF417 | 2D (matrix & stacked) barcodes supported: Dot Code A | Power source type: RS-232

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950