

Logitech Rally Bar



Model: 960-001311

Manufacturer: LOGITECH

EAN: 5099206089327

Product Code: 1250453

R56,463

Minimum system requirements: Internet Connection: Wired or wireless (Rally Bar No-Radio does support WiFi connectivity). USB Mode: Windows 11, Windows 10, the two most recent versions of macOS Appliance Mode: Room solution software license (not included) | Packaging content: Rally Bar Power supply AC power cord HDMI cable USB cable Remote control Lens caps for main camera and AI Viewfinder User documentation | Tilt angle range: -15 - 15° | DC-in jack: Yes | Ethernet LAN data rates: 1000 Mbit/s | Ethernet LAN data rates: 100 | Product colour: Graphite | AC input voltage: 100 - 240 V | Ethernet LAN data rates: 10 | Power source type: AC | Operating temperature (T-T): 0 - 40 °C | USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity: 3 | Cables included: DC | Cables included: AC | USB connector type: USB Type-A | Cables included: USB Type-A to USB Type-C | Operating relative humidity (H-H): 10 - 95% | Package height: 218 mm | Package width: 207 mm | HDMI ports quantity: 3 | Mac operating systems supported: MacOS | HD type: 4K Ultra HD | Package depth: 989 mm | Storage temperature (T-T): -40 - 70 °C | USB connector type: USB Type-C | Weight: 7.08 kg | Quick start guide: Yes | Windows operating systems supported: Yes | Cables included: HDMI | Number of batteries supported: 1 | AC adapter included: Yes | Package weight: 9.3 kg | Security algorithms: 128-bit AES | Noise reduction: Yes | Width: 910 mm | Optical zoom: 5x | Supported video modes: 720p | Supported video modes: 1440p | Supported video modes: 2160p | Supported video modes: 900p | Batteries included: Yes | Wi-Fi: Yes | Built-in speaker(s): Yes | Maximum frame rate: 30 fps |

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

Wi-Fi standards: 802.11b | Zoom capability: Yes | Pan range: -25 - 25° | Remote control included: Yes | Battery technology: Lithium | Supported video modes: 576p | Wi-Fi standards: 802.11g | Battery capacity: 0.675 Wh | Wi-Fi standards: Wi-Fi 4 (802.11n) | Supported network protocols: IPv4, IPv6 | Ethernet LAN: Yes | Depth: 160 mm | Digital zoom: 3x | RMS rated power: 8 W | Height: 164 mm | Product type: Group video conferencing system | Wi-Fi standards: Wi-Fi 5 (802.11ac) | Battery capacity: 220 mAh | Wi-Fi standards: 802.11a | PTZ control: Yes | Microphone in: Yes | Remote control interface: Bluetooth | HDMI output ports quantity: 2 | Power plug type: Type C | Heat dissipation: 64 BTU/h | Current: 4.754 A | Horizontal field of view: 82.1° | Master (outer) case length: 330 mm | Line-out impedance: 4 Ω | HDMI input ports quantity: 1 | Audio beamforming: Yes | DC input voltage: 19 V | Sound pressure level (max): 90 dB | Master (outer) case height: 160 mm | Microphone sensitivity: -36 dB | Echo cancellation: Yes | Microphone frequency: 90 - 16000 Hz | Master (outer) case width: 300 mm | Interface module Ethernet LAN (RJ-45) ports: 1 | Power cable length: 2.5 m | Number of microphones: 6 | HDMI cable length: 2 m | Master (outer) case gross weight: 4.73 kg | Output voltage Total Harmonic Distortion (THD): 2% | Sample rates: 0 - 48 kHz | Diagonal field of view: 90° | Harmonized System (HS) code: 85176990 | Microphone direction type: Omnidirectional | Vertical field of view: 52.2° | Output level: 92/99 dB | Microphone pick-up range: 4.5 m | Telepresence: No

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950