

Akyga AK-B1- 700 power supply unit 700 W 20+4 pin ATX ATX Grey



Model: AK-B1-700

Manufacturer: AKYGA

EAN: 5901720131485

Product Code: 1250489

R1,337

Certification: CE, FCC, RoHS, REACH | PCI Express power cable length: 45 cm | EPS power connector (4+4 pin): Yes | Power Factor Correction (PFC) type: Passive | EPS cable length: 60 cm | Cabling type: Non-Modular | Max output current (+12V): 32 A | Package weight: 1.33 kg | Max output current (-12V): 0.5 A | Total power: 700 W | Fan location: Side | Fan diameter: 12 cm | Combined power (+12V): 384 W | Package height: 95 mm | Peripheral (Molex) power cable length: 300 | Number of SATA power connectors: 5 | Peripheral (Molex) power cable length: 150 mm | SATA power cable length: 300 mm | Motherboard power connector: 20+4 pin ATX | Number of fans: 1 fan(s) | Purpose: PC | Package type: Box | Motherboard power cable length: 45 cm | ATX version: 2.31 | Combined power (+3.3V): 300 W | Height: 85 mm | Power protection features: Short circuit | Power protection features: Over voltage | Power protection features: Over current | Power protection features: Over power | Power protection features: Overheating | Width: 150 mm | Cooling type: Active | Product colour: Grey | Package width: 180 mm | Depth: 160 mm | Efficiency: 70% | Package depth: 260 mm |

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

Power supply unit (PSU) form factor: ATX | Weight: 1.26 kg | On/off switch: Yes | Operating temperature (T-T): 5 - 50 °C | AC input frequency: 50 Hz | Combined power (+5V): 300 W | Combined power (-12V): 18.5 W | Max output current (+3.3V): 35 A | SATA power cable length: 150 | Max output current (+5Vsb): 2.5 A | PCI Express power connectors (6+2 pin): 2 | Peripheral (Molex) power connectors (4-pin): 2 | Max output current (+5V): 38 A | AC input voltage: 220 - 230 V | Mean time between failures (MTBF): 100000 h | Combined power (+5Vsb): 18.5 W | Compliance certificates: RoHS

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950