

CyberPower PR1000ELCD uninterruptible power supply (UPS) Line- Interactive 1 kVA 900 W 8 AC outlet(s)



Model: PR1000ELCD

Manufacturer: CYBERPOWER

EAN: 4712364143809

Product Code: 1250491

R9,774

Certification: CE, EAC, RCM, RoHS | Compatible operating systems: Windows 7 / Vista / XP / 2000, Server 2003 / 2008, Linux | Output frequency: 50/60 Hz | Harmonized System (HS) code: 8504408590 | Waveform: Pure sine | Automatic Voltage Regulation (AVR): Yes | Surge energy rating: 405 J | Hot-swap battery: Yes | UPS topology: Line-Interactive | Number of output IEC jumpers: 1 | AC outlet types: C13 coupler | Output operation voltage (min): 230 V | Operating temperature (T-T): 0 - 40 °C | Input frequency: 50/60 Hz | Weight: 18.9 kg | Form factor: Tower | Package width: 316 mm | Non-operating altitude: 0 - 15000 m | Overload protection: Yes | Response time: 4 ms | Surge protection: Yes | Battery recharge time: 8 h | Serial ports quantity: 1 | Typical backup time at half

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

load: 16 min | Output operation voltage (max): 230 V | Display type: LCD | AC outlets quantity: 8 AC outlet(s) | Housing material: Metal | Power protection features: Overload | Depth: 432 mm | Power factor: 0.9 | Storage relative humidity (H-H): 0 - 95% | Cables included: USB cable | Height: 221 mm | EMI/RFI noise filtering: Yes | USB 2.0 ports quantity: 1 | Input operation voltage (min): 151 V | Power plug: C14 coupler | Typical backup time at full load: 4 min | Input operation voltage (max): 301 V | Operating altitude: 0 - 3000 m | LED indicators: Operation | LED indicators: Error | Product colour: Black | Battery technology: Sealed Lead Acid (VRLA) | Width: 170 mm | Output power: 900 W | Storage temperature (T-T): -15 - 45 °C | Output power capacity: 1 kVA | Operating relative humidity (H-H): 0 - 95% | Package height: 360 mm | Number of batteries supported: 1 | Warnings: Use the appliance in well-ventilated areas to avoid overheating. | Warnings: Keep away from sources of fire and water. | Warnings: Do not disassemble the unit housing, there may be a risk of electric shock.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950