

Chieftec Stealth 1200W Vega M Series SPX- 1200-FC 80+ Platin power supply unit 24- pin ATX ATX Black



Model: SPX-1200-FC

Manufacturer: CHIEFTEC

EAN: 753263079268

Product Code: 1250568

R3,886

Number of EPS connectors: 1 | Number of SATA power cables: 10 | Bearing technology: FDB | Cabling type: Fully-Modular | Total power: 1200 W | ATX version: 3.1 | Max output current (+12V): 100 A | Combined power (+5V): 100 W | Combined power (+12V): 1200 W | Power protection features: Short circuit | Power protection features: Over voltage | Power protection features: Overload | EPS power connector (4+4 pin): Yes | Max output current (+5Vsb): 3 A | PCI Express connector: Yes | Number of SATA power connectors: 8 | Max output current (+5V): 20 A | Combined power (+5Vsb): 15 W | Motherboard power connector: 24-pin ATX | Power protection features: Surge and inrush | Max output current (+3.3V): 20 A | Power Factor Correction (PFC) type: Active | Purpose: PC | PCI Express

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices

may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or

typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

power connectors (6+2 pin): 3 | Power protection features: Under voltage | Power supply unit (PSU)
form factor: ATX | SATA power cable length: 500 mm | Combined power (+3.3V): 100 W | SATA
power cable length: 150 | Fan diameter: 13.5 cm | Peripheral (Molex) power cable length: 150 |
Motherboard power cable length: 60 cm | PCI Express power cable length: 65 cm | Peripheral (Molex)
power cable length: 500 mm | 80 PLUS certification: 80 PLUS Platinum | Width: 150 mm | Input
current: 15.0-7.5 A | AC input voltage: 100 - 240 V | Product colour: Black | Depth: 140 mm | Height:
86 mm | EPS power connector (8-pin): Yes | ATX Power connector (24-pin): Yes | Peripheral (Molex)
power connectors (4-pin): 2 | AC input frequency: 50/60 Hz | Package type: Box | Cooling type: Active

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950