

**GIGABYTE
P550SS ICE
Power Supply -
PCIe 5.0, 80
PLUS Silver,
120mm Fan,
ATX 3.0
compatible, EU
Plug**



Model: GP-P550SS ICE

Manufacturer: GIGABYTE

EAN: 4719331554910

Product Code: 1250609

R1,463

Warranty period: 3 year(s) | Depth: 150 mm | Package weight: 2.11 kg | Package width: 254 mm | Weight: 1.95 kg | AC input frequency: 50/60 Hz | Cooling type: Active | Input current: 6.3 A | AC input voltage: 155-240 V | Peripheral (Molex) power connectors (4-pin): 4 | On/off switch: Yes | Floppy disk drive connector: Yes | Width: 140 mm | Package height: 117 mm | Package depth: 206 mm | Package type: Box | Product colour: White | 80 PLUS certification: 80 PLUS Silver | Total power: 550 W | Number of fans: 1 fan(s) | Fan diameter: 12 cm | Mean time between failures (MTBF): 100000 h |

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

Efficiency: 90% | Power protection features: Under voltage | Power protection features: Over power | Height: 86 mm | Power protection features: Short circuit | Power protection features: Over voltage | Purpose: PC | Power protection features: Over current | Power protection features: Overheating | ATX version: 3.1 | Hold time: 16 ms | Floppy drive power connector: 2 | Max output current (-12V): 0.3 A | Combined power (+3.3V): 100 W | Power Good signal delay range: 100 - 150 ms | Motherboard power cable length: 60 cm | Max output current (+3.3V): 20 A | Power supply unit (PSU) form factor: ATX | PCI Express connector: Yes | Motherboard power connector: 20+4 pin ATX | Combined power (+5V): 100 W | Cabling type: Non-Modular | Max output current (+12V): 45.8 A | Bearing technology: Ball bearing | Power Factor Correction (PFC) type: Active | Fan location: Top | Combined power (-12V): 3.6 W | CPU power connector (4+4 pin): Yes | ATX power connector (20+4 pin): Yes | Max output current (+5V): 20 A | Combined power (+5Vsb): 15 W | Max output current (+5Vsb): 3 A | Number of SATA power connectors: 5 | PCI Express power connectors (6+2 pin): 2 | Combined power (+12V): 549.6 W

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950