

**CyberPower
CP1350EPFCLCD
uninterruptible
power supply
(UPS) Line-
Interactive 1.35
kVA 780 W 6 AC
outlet(s)**



Model: CP1350EPFCLCD

Manufacturer: CYBERPOWER

EAN: 4711027798578

Product Code: 1250695

R6,669

Noise level: 35 dB | Ethernet LAN (RJ-45) ports: 1 | AC outlets quantity: 6 AC outlet(s) | Form factor: Tower | Product colour: Black | Cooling type: Passive | Output power: 780 W | Weight: 10.9 kg | Width: 100 mm | Battery voltage: 12 V | Number of batteries supported: 2 | USB 2.0 ports quantity: 3 | LED indicators: Yes | Battery capacity: 8.5 Ah | Input operation voltage (min): 165 V | Typical backup time at full load: 4 min | EMI/RFI noise filtering: Yes | Cabling technology: 10/100/1000Base-T(X) | Input operation voltage (max): 265 V | Battery recharge time: 8 h | Surge protection features: Fax | Surge protection features: Modem | Surge protection: Yes | Surge protection features: Digital Subscriber Line (DSL) | USB port: Yes | Depth: 370 mm | Output power capacity: 1.35 kVA | Height:

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

265 mm | Power plug: C14 coupler | Typical backup time at half load: 10 min | Display type: LCD | Surge protection features: Network | Surge protection features: Telephone | Modem (RJ-11) ports: 1 | Serial ports quantity: 1 | Audible alarm(s): Yes | Input frequency: 50/60 Hz | Power protection features: Overload | Nominal output voltage: 230 V | Waveform: Sine | Serial interface: Yes | Automatic Voltage Regulation (AVR): Yes | UPS topology: Line-Interactive | Efficiency: 98.5% | Audible alarm modes: Alarm when on battery, Fault, Low battery alarm, Overload alarm | Number of type F outputs: 6 | Warnings: Do not disassemble the unit housing, there may be a risk of electric shock. | Warnings: Use the appliance in well-ventilated areas to avoid overheating. | Sustainability certificates: RoHS | Warnings: Keep away from sources of fire and water. | Output frequency: 50/60 Hz | Auto-restart: Yes

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950