

Gembird EG- UPS-036 uninterruptible power supply (UPS) Line- Interactive 3 kVA 1800 W 6 AC outlet(s)



Model: EG-UPS-036

Manufacturer: ENERGENIE

EAN: 8716309124744

Product Code: 1250706

R4,632

Weight: 19 kg | Sustainability compliance: Yes | Ethernet LAN (RJ-45) ports: 1 | Operating temperature (T-T): 0 - 40 °C | Operating relative humidity (H-H): 20 - 90% | Response time: 10 ms | Noise level: 45 dB | AC outlets quantity: 6 AC outlet(s) | Product colour: Black | Customs product code (TARIC): 8504408590 | Form factor: Compact | Battery voltage: 12 V | USB 2.0 ports quantity: 1 | Compliance certificates: RoHS | Compliance certificates: CE | Battery capacity: 7 Ah | Package type: Box | Warnings: Do not disassemble the unit housing, there may be a risk of electric shock. | Warnings: Keep away from sources of fire and water. | Package width: 300 mm | Typical backup time at half load: 8 min | Charging current: 1.2 A | Typical backup time at full load: 20 min | AC outlet

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

types: C13 coupler | Power protection features: Overcharge | Power protection features: Short circuit
| Output power capacity: 3 kVA | Output operation voltage (max): 220 V | Battery recharge time
(90%): 8 h | Surge protection: Yes | Number of type F outputs: 3 | Output power: 1800 W | Input
frequency: 50/60 Hz | USB port: Yes | Audible alarm(s): Yes | Display type: LCD | Waveform: Sine |
USB port type: USB Type-B | Battery technology: Sealed Lead Acid (VRLA) | AC outlet types: Type F |
Power protection features: Overdischarge | Width: 220 mm | Package height: 150 mm | Number of
batteries supported: 4 | UPS topology: Line-Interactive | Depth: 400 mm | Automatic Voltage
Regulation (AVR): Yes | Cold start: Yes | Input operation voltage (max): 295 V | Input operation
voltage (min): 162 V | Height: 125 mm | Cables included: Input power cable, USB cable | Power plug:
C14 coupler

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950