

Infosec E4 Value 1000 uninterruptible power supply (UPS) Double- conversion (Online) 1 kVA 3 AC outlet(s)



Model: INF_674178

Manufacturer: INFOSEC

EAN: 3700085674178

Product Code: 1250724

R8,448

Certification: CE | Warnings: Do not disassemble the unit housing, there may be a risk of electric shock. | Warnings: Use the appliance in well-ventilated areas to avoid overheating. | Warnings: Store away from sources of heat and open flame. | Compliance certificates: RoHS | Input operation voltage (max): 240 V | Number of input phases: 1 | Serial interface type: RS-232 | Display type: LED | Operating relative humidity (H-H): 20 - 90% | Cold start: Yes | Battery technology: Sealed Lead Acid (VRLA) | Input operation voltage (min): 100 V | Serial ports quantity: 1 | Width: 145 mm | Battery voltage: 12 V | Output operation voltage (max): 240 V | UPS topology: Double-conversion (Online) |

AC outlets quantity: 3 AC outlet(s) | Manual: Yes | Efficiency: 88% | Output voltage regulation: -1 -

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices

may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or

typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

1% | Power factor: 0.8 | Output frequency: 47/63 Hz | Battery recharge time: 4 h | AC outlet types: C13 coupler | Product colour: Black | Cables included: Output power cable, RS-232, Input power cable | Height: 282 mm | Typical backup time at full load: 30 min | ECO mode: Yes | Input power factor: 0.99 | Maximum current: 10 A | Audible alarm(s): Yes | Depth: 220 mm | Output power capacity: 1 kVA | Operating temperature (T-T): 0 - 40 °C | Number of output phases: 1 | Response time: 4 ms | Weight: 8.6 kg | Form factor: Tower | Charging current: 1 A | Serial interface: Yes | Output voltage Total Harmonic Distortion (THD): 6% | Input frequency: 47 - 63 Hz | Audible alarm modes: Alarm when on battery, Fault, Overload alarm, Low battery alarm | Typical backup time at half load: 9 min | Noise level: 50 dB | Crest factor: 3:1 | Output operation voltage (min): 100 V | Battery capacity: 9 Ah | Waveform: Pure sine

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950