

PC Power Supply DEEPCOOL PS750P-FE, Black



Model: R-PS750P-FE0B-JGEU

Manufacturer: DEEPCOOL

EAN: 6933412724513

Product Code: 1253157

R3,337

Certification: CE/FCC/CCC/RCM/EAC/CAN ICES-003(B)/NMB-003(B) /TUV-RH | Width: 125 mm | Power protection features: OCP (overcurrent protection) | Power protection features: OPP (overload protection) | 80 PLUS certification: 80 PLUS Bronze | Mean time between failures (MTBF): 100000 h | Input current: 10 - 5 A | AC input voltage: 100 - 240 V | Power protection features: OTP (overheat protection) | Height: 63.5 mm | Product colour: Black | Total power: 750 W | Cabling type: Modular | Purpose: PC | Power protection features: NLO | AC input frequency: 50/60 Hz | On/off switch: Yes | Fan diameter: 9.2 cm | ATX version: 3.1 | Depth: 100 mm | Efficiency: 92.41% | Number of fans: 1 fan(s) | Cooling type: Active | Operating temperature (T-T): 0 - 50 °C | Power protection features: SIP (surge and shock protection) | Power protection features: SCP (short circuit protection) | Power protection features: OVP (overvoltage protection) | Power supply unit (PSU) form factor: SFX | Power protection features: UVP (undervoltage protection) | Package type: Box | PCI Express power connectors (6+2 pin): 3 | Peripheral (Molex) power connectors (4-pin): 2 | Max output current

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

(+12V): 62.5 A | CPU power connector (4+4 pin): Yes | Sustainability compliance: Yes | Number of SATA power connectors: 6 | ATX power connector (20+4 pin): Yes | Motherboard power cable length: 30 cm | Power Good signal delay range: 100 - 150 ms | Motherboard power connector: 20+4 pin ATX | Power Factor Correction (PFC) type: Active | Bearing technology: Fluid Dynamic Bearing (FDB) | Fan location: Top | Compliance certificates: RoHS | Compliance certificates: CE | Compliance certificates: Federal Communications Commission (FCC) | Combined power (+12V): 750 W | PCI Express power connectors (16-pin): 1

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950