

PC Power Supply DEEPCOOL PS850P-FE, Black



Model: R-PS850P-FE0B-JGEU

Manufacturer: DEEPCOOL

EAN: 6933412724650

Product Code: 1253158

R3,637

Certification: CE/FCC/CCC/RCM/EAC/CAN ICES-003(B)/NMB-003(B) /TUV-RH | AC input frequency: 50/60 Hz | Operating temperature (T-T): 0 - -40 °C | Cooling type: Active | Product colour: Black | AC input voltage: 100 - 240 V | Power protection features: OCP (overcurrent protection) | Power protection features: OTP (overheat protection) | Fan location: Top | Power Factor Correction (PFC) type: Active | Height: 63.5 mm | Max output current (+12V): 70.8 A | On/off switch: Yes | Bearing technology: Fluid Dynamic Bearing (FDB) | Width: 125 mm | Number of fans: 1 fan(s) | Input current: 13 - 6.5 A | Mean time between failures (MTBF): 100000 h | Fan diameter: 9.2 cm | ATX version: 3.1 | Motherboard power cable length: 35 cm | Power protection features: SCP (short circuit protection) | Power protection features: UVP (undervoltage protection) | Power protection features: OVP (overvoltage protection) | Power protection features: OPP (overload protection) | Power protection features: SIP (surge and shock protection) | Cabling type: Modular | PCI Express power connectors (6+2 pin): 3 | Peripheral (Molex) power connectors (4-pin): 2 | Total power: 850 W | Package type:

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

Box | Depth: 100 mm | Efficiency: 92% | Power protection features: NLO | 80 PLUS certification: 80 PLUS Gold | Purpose: PC | Combined power (+12V): 850 W | Motherboard power connector: 20+4 pin ATX | Power supply unit (PSU) form factor: SFX | Compliance certificates: RoHS | Compliance certificates: CE | PCI Express power connectors (16-pin): 1 | Compliance certificates: Federal Communications Commission (FCC) | Sustainability compliance: Yes | Number of SATA power connectors: 6 | ATX power connector (20+4 pin): Yes | Power Good signal delay range: 100 - 150 ms | CPU power connector (4+4 pin): Yes

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950