

Thermaltake Toughpower Gt power supply unit 850 W 24- pin ATX ATX Black



Model: PS-TPT-0850FNFACE-3

Manufacturer: THERMALTAKE

EAN: 4711475647411

Product Code: 1257558

R2,445

Certification: CE/UKCA/ICES/TUV/LVD/RCM/CB/FCC/cTUVus/BSMI/CCC/BIS/S-MARK | PCI Express power connectors (12+4 pin) cable length: 600 mm | PCI Express power connectors (12+4 pin): 1 | Max output current (+3.3V): 20 A | Power Good signal delay range: 100 - 250 ms | AC input frequency: 50/60 Hz | Operating temperature (T-T): 0 - 40 °C | Bearing technology: Hydraulic | Total power: 850 W | PCI Express power connectors (6+2 pin): 4 | Cabling type: Fully-Modular | Max output current (+5Vsb): 3 A | Combined power (+12V): 850 W | Power protection features: Overheating | Combined power (-12V): 3.6 W | Power protection features: Over power | SATA power cable length: 150 | Power protection features: Under voltage | Power protection features: Over current | Product colour: Black | Purpose: PC/Server | Power protection features: Short circuit | Power protection features: Over voltage | Width: 150 mm | Hold time: 17 ms | Motherboard power connector: 24-pin ATX | Combined power (+5Vsb): 15 W | Package type: Box | SATA power cable length: 450 | CPU power connector

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

(4+4 pin): Yes | Max output current (+5V): 20 A | Peripheral (Molex) power cable length: 150 | CPU power cable length: 70 cm | Number of fans: 1 fan(s) | Motherboard power cable length: 55 cm | Height: 86 mm | Mean time between failures (MTBF): 100000 h | Depth: 140 mm | On/off switch: Yes | Storage relative humidity (H-H): 5 - 95% | Peripheral (Molex) power cable length: 400 mm | ATX version: 3.1 | Input current: 10 A | Storage temperature (T-T): -40 - 70 °C | Peripheral (Molex) power connectors (4-pin): 4 | 80 PLUS certification: 80 PLUS Gold | Max output current (+12V): 70.8 A | Combined power (+5V): 100 W | Fan diameter: 12 cm | Combined power (+3.3V): 100 W | Number of SATA power connectors: 6 | Power Factor Correction (PFC) type: Active | Power supply unit (PSU) form factor: ATX | Operating relative humidity (H-H): 5 - 85% | Max output current (-12V): 0.3 A | Cooling type: Active | AC input voltage: 100 - 240 V

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950