

IP CAMERA DAHUA IPC- HFW2849S-S-IL- 0280B



Model: IPC-HFW2849S-S-IL-0280B

Manufacturer: DAHUA

EAN: 6923172581570

Product Code: 1257864

R3,363

Certification: LVD: EN62368-1 EMC: Electromagnetic Compatibility Directive 2014/30/EU FCC: 47 CFR FCC Part 15, Subpart B 2023-02-22 | Lens viewing angle, vertical: 58° | Lens viewing angle, horizontal: 111° | Lens viewing angle, diagonal: 132° | Number of lenses: 1 | Lens type: Fixed focal length lens | Warnings: The product contains electronic components do not dispose of with the normal household waste. | Warnings: Avoid direct contact with water to prevent electrical damage. | Warnings: Ensure that the product is properly installed and protected against falling. | Ethernet LAN: Yes | White balance: Outdoor | White balance: Manual | Night vision distance: 30 m | Depth: 166.2 mm | White balance: Natural | Audio formats supported: G.711a | Sensor type: CMOS | Wide Dynamic Range (WDR): 120 dB | Bit rate: H.264: 32 kbps-8192 kbps H.265: 12 kbps-8192 kbps | Power consumption (Power over Ethernet (PoE)): 5.9 W | Housing material: Metal | Form factor: Tube/dome | Quality of Service (QoS) support: Yes | Built-in HDD: No | LED type: IR / White light LED | Audio formats supported: PCM | Region of Interest (ROI) encoding: Yes | Progressive scan: Yes | Minimum illumination: 0.008 lx | Total megapixels: 8 MP | Adjustment shutter speed: Auto/Manual | Highlight Compensation (HLC): Yes | Power consumption (max): 5 W | Maximum resolution: 3840 x 2160 pixels

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

| Ethernet interface type: Fast Ethernet | Tilt angle range: 0 - 90° | Gain control type: Auto/Manual | White balance: Auto | Audio formats supported: G.726 | Wi-Fi: No | Internal memory: 256 MB | Back Light Compensation (BLC): Yes | Video motion detection: Yes | Weight: 470 g | Supported graphics resolutions: 2048 x 1536 (QXGA) | Supported graphics resolutions: 3072 x 1728 | Width: 70 mm | Mounting type: Ceiling/wall | Product colour: White | Placement supported: External / Internal | Noise reduction technology: 3D noise reduction | Storage temperature (T-T): -40 - 55 °C | Height: 70 mm | Power source type: DC, PoE | Type: IP security camera | Audio formats supported: G.711Mu | Video streaming: Yes | Supported graphics resolutions: 704 x 576 | Supported graphics resolutions: 1280 x 960 | Supported graphics resolutions: 3072 x 2048 | Number of sensors: 1 | Operating temperature (T-T): -40 - 55 °C | Web browser: Yes | International Protection (IP) code: IP67 | Supported graphics resolutions: 1280 x 720 | Supported graphics resolutions: 2880 x 1620 | Supported graphics resolutions: 352 x 240 | Supported graphics resolutions: 2304 x 1296 | Supported graphics resolutions: 3840 x 2160 | Number of cameras: 1 | Supported graphics resolutions: 704 x 480 | Supported graphics resolutions: 2688 x 1520 | Supported graphics resolutions: 1920 x 1080 | Number of illumination LEDs: 2 | Camera shutter speed: 1/3 - 1/100000 s | Bit rate control: Constant Bit Rate (CBR)/Variable Bit Rate (VBR) | Frame rate: 30 fps | Night vision: Yes | Built-in microphone: Yes | Power consumption (typical): 2.7 W | Operating relative humidity (H-H): 0 - 95% | Web-based management: Yes | Optical sensor size: 25.4 / 2.7 mm (1 / 2.7") | Noise reduction: Yes | Supported graphics resolutions: 352 x 288 | Video compression formats: H.265+ | Networking standards: IEEE 802.3af | Video compression formats: H.265 | Maximum aperture number: 1.6 | DC output voltage: 12 | Video compression formats: H.264 | Bluetooth: No | Video compression formats: H.264H | Connectivity technology: Wired | Video compression formats: M-JPEG | Video compression formats: H.264B | Focal length range: 2.8 mm | Number of users: 20 user(s) | Video compression formats: H.264+ | Pan range: 0 - 360° | White balance: Street lamp | ROM capacity: 128 MB | Mobile operating systems supported: iOS | Closest focusing distance: 1.5 m | Mobile operating systems supported: Android

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950