

GODOX TT685II TTL Flash for Sony



Model: TT685IIS

Manufacturer: GODOX

EAN: 6952344223697

Product Code: 1275528

R3,861

GODOX TT685IIS Flash

The GODOX TT685IIS flash for Sony is an advanced news flash designed for Sony cameras. It offers a guide number of 60 (ISO 100, 200 mm), 76Ws of power, TTL automatic light metering, and HSS synchronization with short shutter speeds up to 1/8000 s. The color temperature of 5600 K (± 200 K) ensures natural color reproduction and facilitates working with other light sources. The model is also equipped with a swivel head with a 20–200 mm zoom range, a built-in Godox X 2.4 GHz radio system, and a clear LCD display, making it ideal for wedding, portrait, documentary, and event photography.

High Power and Precise Lighting

A guide number of 60 and a flash energy output of 76Ws allow for effective lighting of both individual subjects and larger scenes. As a result, the flash performs well both indoors and outdoors, offering great flexibility in selecting exposure settings. TTL automatic mode helps you quickly—

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

achieve properly exposed photos even under rapidly changing lighting conditions. HSS synchronization up to 1/8000 of a second enables shooting with very fast shutter speeds, making it easier to control ambient light and achieve an attractively blurred background.

Built-in Godox X Radio System

The TT685IIS model is equipped with an integrated 2.4 GHz Godox X radio system, which allows it to function as both a transmitter and a receiver. With a range of up to 100 meters, support for 32 channels, and five groups, it makes it easy to set up complex lighting rigs without the need for cables. The flash is compatible with popular Godox models, such as the V1, AD200Pro, and AD300Pro, as well as the X1, X2, and XPro transmitters. This allows you to easily expand your lighting system and control multiple flashes simultaneously.

Flexible Head and Wide Zoom Range

The flash head offers automatic and manual zoom ranging from 20 to 200 mm, allowing you to adjust the beam width to match your lens and the scene you're photographing. This feature increases the efficiency of light usage and makes it easier to achieve the desired lighting effect. The head can be tilted from -7° to 120° and rotated 330°, providing great flexibility when bouncing light off walls and ceilings. This makes it easier to achieve soft, natural-looking lighting in both portrait and event photography.

Intuitive operation and extensive triggering options

The flash is equipped with a TCM (TTL Converted to Manual) function, which allows you to quickly switch from automatic TTL mode to manual settings while maintaining the selected exposure. This feature significantly streamlines workflow during a shoot and allows you to switch to manual flash power control more quickly. The clear, backlit LCD display makes it easy to adjust settings even in low-light conditions. The flash can be triggered via a hot shoe, the Godox X radio system, a test button, or via a 2.5 mm sync port, providing great flexibility during use.

Included

- **GODOX TT685IIS Flash**

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

- Stand
- Protective case
- Manufacturer's packaging

Manufacturer	GODOX
Model	TT685IIS
Compatibility	Sony
Guide number	60 (ISO 100, 200 mm)
Flash power	76 Ws
Color temperature	5600 K ±200 K
Operating modes	TTL, Manual
HSS sync	up to 1/8000 s
Head zoom	20-200 mm (automatic and manual)
Vertical head tilt range	from -7° to +120°
Horizontal head rotation range	330°
Radio system	Godox X 2.4 GHz
Transmission range	up to 100 m
Channels / groups	32 / 5
Power control	via the flash unit and the Godox X system
Triggering methods	hot shoe, Godox X system, test button, 2.5 mm sync port
Display	backlit LCD
Power supply	4 × AA (R6) batteries – not included
Maximum recharge time	2.6 s
Battery pack slot	yes
USB-C port	yes (software update)

Gross weight: 540, Net weight: 460, Box length: 18,50, Box width: 7,50, Box height: 11,00, Set: Yes, With tripod: Yes, Adjustable intensity: Yes, GPSR Link: https://psr-assets.innpro.pl/photo_and_accessories/sg_photo_and_accessories_photographic_studio.pdf,

Information about data generation: <https://dataact.innpro.pl/GODOX/6952344223697>, PPWR:

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

