

**Hikvision Pro
Series DS-
2CD2066G2H-
IU(2.8mm)(eF)/BLACK
Indoor/Outdoor
IP Security
Bullet Camera
3200 x 1800 px
Ceiling/Wall**



Model: DS-2CD2066G2H-IU

Manufacturer: HIKVISION

EAN: 6942160480398

Product Code: 1275593

R4,574

Built-in HDD: No | DC output current: 0.58 A | HTTPS encryption: Yes | Detect distance: 64 m |
Observe distance: 25 m | Lens viewing angle, vertical: 60° | Maximum aperture number: 1 | Video
compression formats: H.265+ | Video compression formats: H.265 | Video compression formats:
H.264+ | Video compression formats: M-JPEG | Digest authentication: Yes | Frame rate: 30 fps | Fixed
focal length: 2.8 mm | Progressive scan: Yes | Signal-to-Noise Ratio (SNR): 52 dB | Placement
supported: Indoor & outdoor | Video motion detection: Yes | Privacy masking: Yes | Audio formats

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices
may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or
typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

supported: G.722.1 | Sensor type: CMOS | Bit rate control: Constant Bit Rate (CBR)/Variable Bit Rate (VBR) | Region of Interest (ROI) encoding: Yes | Audio formats supported: G.726 | Noise reduction: Yes | Mounting type: Ceiling/wall | Day/night mode: Yes | Optical sensor size: 25.4 / 2.4 mm (1 / 2.4") | Video compression formats: H.264 | Noise reduction technology: 3D noise reduction | Audio formats supported: AAC-LC | Lens viewing angle, diagonal: 143.5° | IP address filtering: Yes | Image quality adjustment: Saturation | Bit rate range: 8 - 320 Kbit/s | Lens viewing angle, horizontal: 114.8° | Sample rates: 8 - 48 kHz | Intelligent Video Surveillance (IVS) system features: Intrusion | Image quality adjustment: Contrast | DC output voltage: 12 | Intelligent Video Surveillance (IVS) system features: Vehicle detection | Intelligent Video Surveillance (IVS) system features: Region entrance detection | Mirror: Yes | Infrared (IR) cut-off filter: Yes | Recognize distance: 12 m | Intelligent Video Surveillance (IVS) system features: Line crossing detection | Password protection: Yes | Image quality adjustment: Brightness | Pixel counter: Yes | Night vision: Yes | Intelligent Video Surveillance (IVS) system features: Scene change | Image quality adjustment: Sharpness | Number of lenses: 1 | Intelligent Video Surveillance (IVS) system features: Human detection | Number of simultaneous live view channels: 6 channels | Number of users: 32 user(s) | Audio formats supported: MP2L2 | Intelligent Video Surveillance (IVS) system features: Region exiting detection | Heartbeat: Yes | Dynamic range: 120 dB | User access level: Administrator, Operator, User | Languages support: Multi | Infra-red wavelength: 850 nm | Identify distance: 6 m | Digital watermark: Yes | Active tampering alarm: Yes | Password reset via email: Yes | Supported graphics resolutions: 640 x 480 (VGA) | Card reader integrated: Yes | Maximum resolution: 3200 x 1800 pixels | Lens mount interface: M12 | Form factor: Bullet | Package width: 234 mm | Reset button: Yes | Diameter: 7.44 cm | Supported graphics resolutions: 640 x 360 | Ethernet LAN: Yes | Angle of rotation: 360° | Audio formats supported: PCM | Power source type: DC, PoE | Supported graphics resolutions: 3200 x 1800 | Pan range: 0 - 360° | Tilt angle range: 0 - 90° | Supported graphics resolutions: 2688 x 1520 | Built-in microphone: Yes | Number of cameras: 1 | Compatible memory cards: MicroSDHC | Highlight Compensation (HLC): Yes | International Protection (IP) code: IP67 | Audio formats supported: MP3 | Audio formats supported: G.711 | Package weight: 815 g | Supported graphics resolutions: 1920 x 1080 (HD 1080) | Supported graphics resolutions: 1280 x 720 (HD 720) | Storage temperature (T-T): -30 - 60 °C | Compatible memory cards: MicroSDXC | Wide Dynamic Range (WDR): Yes | Product colour: Black | Compatible memory cards: MicroSD (TransFlash) | Package height: 117 mm | Ethernet interface type: Fast Ethernet | Operating relative humidity (H-H): 0 - 95% | Package depth: 120 mm | Bluetooth: No | Camera shutter speed: 1/3 s - 1/100000 | Total megapixels: 6 MP | Protection features: Dust resistant | Connectivity technology: Wired | Protection features: Water resistant | LED type: IR | Weight: 505 g | **Power consumption (max): 8.5 W | Depth: 179.2 mm | Night vision distance: 40 m | Bit rate: 32**

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

Kbps - 16 Mbps | Wi-Fi: No | Operating temperature (T-T): -30 - 60 °C | Minimum illumination: 0 lx | Ethernet LAN (RJ-45) ports: 1 | Back Light Compensation (BLC): Yes | Video formats supported: H.264+ | Security algorithms: EAP-MD5 | Video formats supported: H.264 | Storage relative humidity (H-H): 0 - 95% | Video formats supported: H.265+ | Video formats supported: H.265 | Type: IP security camera | Networking standards: IEEE 802.1x | Networking standards: IEEE 802.3af | Security algorithms: TLS | Housing material: Metal | Security algorithms: EAP-LEAP | Video formats supported: M-JPEG | Security algorithms: EAP-TLS | Compliance certificates: KC | Compliance certificates: Low Voltage Directive (LVD) | Compliance certificates: UKCA | Compliance certificates: Electromagnetic Compatibility (EMC) | Compliance certificates: RoHS | Compliance certificates: WEEE | Compliance certificates: RCM | Compliance certificates: REACH | Compliance certificates: CB | Audit log: Yes | Number of Privacy masking areas: 4

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950