

**Ubiquiti UniFi
Pro XG 48 PoE
Managed L3 10G
Ethernet
(100/1000/10000)
Power over
Ethernet (PoE)
1U Grey**



Model: USW-Pro-XG-48-PoE

Manufacturer: UBIQUITI

EAN: 810177160748

Product Code: 1275621

R57,531

10G Ethernet (copper) ports quantity: 32 | SFP28 ports quantity: 4 | 2.5G Ethernet (copper) ports quantity: 16 | IPv4 routes: 256000 | Rack mount kit: Yes | Forwarding rate: 684 Mpps | Flow control support: Yes | Broadcast storm control: Yes | Throughput: 460 Gbit/s | Virtual LAN features: Interface-based VLAN | Stackable: Yes | Access Control List (ACL) IPv4 entries: 256 | Static route: Yes | Switch layer: L3 | Virtual LAN features: Voice VLAN | Backlight display: Yes | Power over Ethernet (PoE) type supported: PoE+++ | Rate limiting: Yes | Loop protection: Yes | Switch type: Managed | Compliance certificates: CE | Compliance certificates: Industry Canada (IC) | Compliance certificates: National Defense Authorization Act (NDAA) | Compliance certificates: Federal Communications Commission

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

(FCC) | Reset button: Yes | 10G support: Yes | Product colour: Grey | Quality of Service (QoS) support: Yes | Height: 44 mm | Number of VLANs: 1000 | Cables included: Power | Width: 442 mm | DHCP features: DHCP guarding | DHCP features: DHCP server | Power over Ethernet (PoE): Yes | Form factor: 1U | DHCP features: DHCPv6 snooping | DHCP features: DHCP relay | IGMP snooping: Yes | Rack mounting: Yes | Jumbo frames support: Yes | AC input frequency: 50/60 Hz | Power supply included: Yes | AC input voltage: 100 - 240 V | Display type: LCM | Operating relative humidity (H-H): 10 - 90% | Weight: 8.7 kg | Power consumption (max): 1280 W | Basic switching RJ-45 Ethernet ports quantity: 48 | Operating temperature (T-T): -5 - 40 °C | Power source: AC/DC | Total Power over Ethernet (PoE) budget: 1080 W | Depth: 480 mm | VLAN support: Yes | Multicast support: Yes | Redundant power supply (RPS) support: Yes | Housing material: SGCC | Basic switching RJ-45 Ethernet ports type: 10G Ethernet (100/1000/10000) | Power connector: AC/DC | Power over Ethernet (PoE) power per port: 15.4 W | Packet buffer memory: 8 MB | Switching capacity: 920 Gbit/s | Port mirroring: Yes | MAC address table: 128000 entries

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950