

HIKVISION DS- 2SE4C425MWG- E/26(F0) IP Camera



Model: DS-2SE4C425MWG-E/26(F0)

Manufacturer: HIKVISION

EAN: 6931847199630

Product Code: 1278348

R11,726

Product colour: Black | Tilt angle range: 0 - 90° | Maximum resolution: 3632 x 1632 pixels | Bit rate: 32 Kbps - 16 Mbps | Weight: 2.4 kg | Power consumption (max): 24 W | Connectivity technology: Wired | Product colour: White | Ethernet LAN: Yes | Supported graphics resolutions: 1920 x 1080 (HD 1080) | Supported graphics resolutions: 3632 x 1632 | Supported graphics resolutions: 704 x 576 | Supported graphics resolutions: 1280 x 960 | Supported graphics resolutions: 1200 x 536 | Supported graphics resolutions: 352 x 288 | Supported graphics resolutions: 352 x 240 | Supported graphics resolutions: 2560 x 1440 | Supported graphics resolutions: 960 x 432 | Compatible memory cards: MicroSD (TransFlash) | Height: 375 mm | Supported graphics resolutions: 1280 x 720 (HD 720) | Supported graphics resolutions: 640 x 480 (VGA) | Supported graphics resolutions: 704 x 480 | Operating relative humidity (H-H): 0 - 90% | Ethernet interface type: Fast Ethernet | Ethernet LAN (RJ-45) ports: 1 | Compatible memory cards: MicroSDXC | Compatible memory cards: MicroSDHC | Protection features: Waterproof | International Protection (IP) code: IP66 | Operating temperature (T-T): -30 - 65 °C | Type: IP security camera | Quality of Service (QoS) support: Yes | Wide Dynamic Range (WDR): Yes | Card reader integrated: Yes | Power source type: PoE+, DC | Zoom speed: 3.6 s |

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

Number of simultaneous live view channels: 20 channels | Automatic Network Replenishment (ANR): Yes | IP address filtering: Yes | Alarm output channels: 1 | Audio formats supported: G.711 | Video motion detection: Yes | Privacy masking: Yes | PTZ status display: Yes | Highlight Compensation (HLC): Yes | Optical zoom: 25x | Audio formats supported: MP3 | Video compression formats: H.265 | Audio formats supported: PCM | Alarm input channels: 1 | Supported network protocols: IPv4/IPv6, HTTP, HTTPS, QoS, 802.1x, FTP, SMTP, UPnP, SNMP, DNS, DDNS, NTP, RTSP, RTCP, RTP, TCP/IP, DHCP, PPPoE, Bonjour | Region of Interest (ROI) encoding: Yes | Audio formats supported: G.726 | Client interoperability: iVMS-4200, Hik-Connect | Pan range: 360 | Lens viewing angle, diagonal: 61.5 - 2.8° | Mounting type: Ceiling | DC output voltage: 12 | Lens viewing angle, horizontal: 55 - 2.4° | Number of cameras: 1 | Zoom capability: Yes | PTZ control: Yes | Product diameter: 166 mm | Lens viewing angle, vertical: 33 - 1.4° | LED type: IR | Audio formats supported: G.722.1 | Sensor type: CMOS | Video compression formats: H.264 | Total megapixels: 6 MP | Camera shutter speed: 1 - 1/30000 s | Audio formats supported: AAC-LC | Day/night mode: Yes | Minimum illumination: 0 lx | Auto focus: Yes | Number of users: 32 user(s) | Video compression formats: M-JPEG | Digital zoom: 16x | Alarm input/output: Yes | Progressive scan: Yes | Frame rate: 25 / 30 fps | Audio formats supported: MP2L2 | Placement supported: Outdoor | Maximum memory card size: 256 GB | Night vision: Yes | Preset programs quantity: 300 | Password protection: Yes | Digital watermark: Yes | Live view: Yes | Built-in speaker(s): Yes | Dynamic range: 120 dB

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950