

**CyberPower
BR700ELCD-FR
uninterruptible
power supply
(UPS) Line-
Interactive 0.7
kVA 420 W 8 AC
outlet(s)**



Model: BR700ELCD-FR

Manufacturer: CYBERPOWER

EAN: 4712856271225

Product Code: 1278753

R3,097

Certification: CE | Display type: LCD | Automatic Voltage Regulation (AVR): Yes | AC outlet types: Type E | Surge protection features: Network | Surge protection features: Telephone | Depth: 288 mm | Operating altitude: 0 - 3000 m | Waveform: Sine | Output power: 420 W | Operating temperature (T-T): 0 - 40 °C | Cold start: Yes | Cable length: 1.5 m | Housing material: Plastic | Typical backup time at half load: 6 min | Storage relative humidity (H-H): 0 - 90% | Output power capacity: 0.7 kVA | UPS topology: Line-Interactive | Response time: 4 ms | Weight: 5.3 kg | AC outlets quantity: 8 AC outlet(s) | Warnings: Use the appliance in well-ventilated areas to avoid overheating. | Audible alarm(s): Yes |

Warnings: Do not disassemble the unit housing, there may be a risk of electric shock. | Surge energy

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices

may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or

typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

rating: 125 J | Non-operating altitude: 0 - 3000 m | Ethernet LAN (RJ-45) ports: 2 | Input frequency: 50/60 Hz | Height: 118 mm | Product colour: Black | Storage temperature (T-T): -20 - 50 °C | Surge protection features: Modem | Form factor: Compact | Surge protection features: Digital Subscriber Line (DSL) | Warnings: Keep away from sources of fire and water. | Width: 166 mm | Operating relative humidity (H-H): 0 - 90% | Surge protection: Yes | USB port: Yes | Power protection features: Overload | Output frequency: 50/60 Hz | EMI/RFI noise filtering: Yes | Audible alarm modes: Alarm when on battery, Fault, Low battery alarm, Overload alarm | Surge protection features: Fax | Typical backup time at full load: 2 min | Modem (RJ-11) ports: 2 | Battery recharge time: 8 h | Battery technology: Sealed Lead Acid (VRLA) | LED indicators: Yes | Compliance certificates: RoHS | USB 2.0 ports quantity: 1 | Input operation voltage (max): 290 V | Input operation voltage (min): 165 V

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950