

Hikvision DS- 2CD1161G2-LIU IP camera



Model: DS-2CD1161G2-LIU

Manufacturer: HIKVISION

EAN: 6936422131012

Product Code: 1279173

R2,218

Tilt angle range: 0 - 75° | Weight: 550 g | Connectivity technology: Wired | Night vision distance: 30 m | Ethernet LAN data rates: 10,100 Mbit/s | LED type: IR/White | International Protection (IP) code: IP67 | Power over Ethernet (PoE): Yes | Ethernet LAN: Yes | Built-in microphone: Yes | Depth: 97.6 mm | Compatible memory cards: MicroSDHC | Number of cameras: 1 | Form factor: Dome | Wide Dynamic Range (WDR): 120 dB | Quality of Service (QoS) support: Yes | Package depth: 150 mm | Operating temperature (T-T): -30 - 60 °C | Compatible memory cards: MicroSDXC | Bit rate: 32 Kbps - 16 Mbps | Package height: 141 mm | Operating relative humidity (H-H): 0 - 95% | Ethernet LAN (RJ-45) ports: 1 | Storage temperature (T-T): -30 - 60 °C | Compatible memory cards: MicroSD (TransFlash) | Package width: 150 mm | Package weight: 800 g | Maximum resolution: 3200 x 1800 pixels | Product colour: White | Web-based management: Yes | Housing material: Plastic | Housing material: Metal | Type: IP security camera | Storage relative humidity (H-H): 0 - 95% | Highlight Compensation (HLC): Yes | Minimum illumination: 0 lx | Video motion detection: Yes | Recognize distance (wide): 23 m | Power management: DC 12 V | Sensor type: CMOS | Angle of rotation: 355° | Progressive scan: Yes | Maximum frame rate: 20 fps | Noise filter: Yes | Diameter: 12.1 cm | DC output current: 0.5 A | Night vision: Yes | Pan range: 0 - 355° | Total megapixels: 6 MP | Infra-red

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

wavelength: 850 nm | Camera shutter speed: 1/3 - 1/100000 s | Region of Interest (ROI) encoding: Yes | Optical sensor size: 25.4 / 2.4 mm (1 / 2.4") | Sample rate: 8 kHz / 16 kHz | Number of users: 32 user(s) | Bit rate control: Constant Bit Rate (CBR)/Variable Bit Rate (VBR) | Heartbeat: Yes | Video compression formats: H.265+ | Password protection: Yes | Video compression formats: H.264 | Observe distance (wide): 45 m | Video compression formats: M-JPEG | Detect distance (wide): 115 m | Maximum aperture number: 1.6 | Video compression formats: H.265 | Mirror: Yes | Signal-to-Noise Ratio (SNR): 52 dB | Day/night mode: Yes | Video compression formats: H.264+ | Maximum memory card size: 512 GB | Identify distance (wide): 11 m | Lens viewing angle, diagonal: 127 - 96° | Lens viewing angle, vertical: 55 - 38° | Lens viewing angle, horizontal: 105 - 78° | Sustainability certificates: REACH | Sustainability certificates: WEEE | Mono sound: Yes | PoE standard: IEEE 802.3af

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950