

Thermaltake TOUGHPower GF A3 power supply unit 1050 W 24-pin ATX ATX Black



Model: PS-TPD-1050FNFAGE-H

Manufacturer: THERMALTAKE

EAN: 4713227537612

Product Code: 1279661

R3,172

Certification: CE/FCC/UKCA/ICES/LVD/TUV/cTUVus/CB/CCC/BSMI | Floppy disk drive cable length: 15 cm | EPS power connector (4+4 pin): Yes | Motherboard power connector: 24-pin ATX | Combined power (+12V): 1050 W | Storage relative humidity (H-H): 5 - 95% | Operating temperature (T-T): 0 - 45 °C | Number of fans: 1 fan(s) | Max output current (+12V): 87.5 A | ATX version: 3.0 | Purpose: PC | SATA power cable length: 650 | SATA power cable length: 950 mm | Max output current (+5V): 20 A | PCI Express power connectors (12+4 pin) cable length: 600 mm | Cabling type: Fully-Modular | SATA power cable length: 800 mm | Max output current (+3.3V): 20 A | Total power: 1050 W | Peripheral (Molex) power cable length: 650 | Motherboard power cable length: 60 cm | Width: 150 mm | Floppy disk drive connector: Yes | Peripheral (Molex) power cable length: 500 mm | Peripheral (Molex) power cable length: 800 | Max output current (+5Vsb): 3 A | Number of SATA power connectors: 12 | Product colour: Black | PCI Express power connectors (12+4 pin): 1 | SATA power

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

cable length: 500 mm | Peripheral (Molex) power connectors (4-pin): 4 | Storage temperature (T-T): -40 - 70 °C | Combined power (-12V): 3.6 W | Height: 86 mm | Power Factor Correction (PFC) type: Active | Input current: 16 A | Mean time between failures (MTBF): 100000 h | Depth: 140 mm | Combined power (+5Vsb): 15 W | 80 PLUS certification: 80 PLUS Gold | AC input frequency: 50/60 Hz | AC input voltage: 100 - 240 V | Power supply unit (PSU) form factor: ATX | PCI Express power connectors (6+2 pin): 5 | Fan diameter: 12 cm | Peripheral (Molex) power cable length: 950 mm | Operating relative humidity (H-H): 5 - 85% | Bearing technology: FDB | Combined power (+3.3V): 100 W | Combined power (+5V): 100 W

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950