

QiDi Q2 Combo 3D printer



Model: Q2 Combo

Manufacturer: QIDI

EAN: 744581222924

Product Code: 1292285

R17,835

QiDi Q2 Combo 3D printer

The QiDi Q2 Combo 3D printer has been designed for people who expect high-quality prints and stable operation even at high speeds. The device combines a precise leveling system, a modern CoreXY design, and an efficient hotend with a temperature of up to 370°C. This allows the printer to handle both popular filaments and more demanding technical materials. The solutions used improve print repeatability, reduce first layer errors, and improve the overall surface quality of models.

A new generation of automatic leveling

The QiDi Q2 Combo uses a leveling sensor in which the nozzle itself acts as the sensor. This means actual contact with the table surface, without the need for an offset probe. This eliminates errors resulting from inaccurate measurements or differences in the table surface. Automatic leveling is completely maintenance-free and allows you to quickly prepare the printer for operation, ensuring accurate placement of the first layer.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

High speed and precise movement

The CoreXY design and the new 1.5GT belt with higher tooth density ensure smoother head movement. This reduces vibration and limits the formation of artifacts visible on the surface of prints. Intelligent resonance control further stabilizes the mechanism, so even at high speeds, the printer maintains good detail quality and smooth model surfaces.

Efficient hotend for technical materials

The new hotend design allows operation at temperatures up to 370°C. The ceramic throat and redesigned heat dissipation system help reduce the risk of nozzle clogging during long prints. The bimetallic hardened steel nozzle increases wear resistance, which is especially important when working with filaments containing carbon or glass fibers.

Stable working chamber and temperature control

The printer is equipped with a second-generation heated working chamber that can reach temperatures of up to 65°C. This makes it possible to print more demanding materials, such as ABS or PC, with less risk of deformation. The heated bed with an aluminum base and double-sided PEI plate ensures good adhesion of models and facilitates their removal after printing.

Smart features and operation monitoring

The QiDi Q2 Combo offers a set of features that support convenient operation. The camera allows you to preview your print in up to 1080p resolution and create timelapse recordings. Sensors detect when filament is running low, and the optional QIDI Box system allows for multi-color printing and material entanglement detection. The power failure recovery system allows you to continue printing without having to start over from the beginning.

AI camera and print error detection

The QiDi Q2 Combo printer is equipped with an AI camera that monitors the printing process and helps detect potential problems during operation. The system analyzes the image in real time and can detect irregularities such as the so-called "spaghetti" effect, which occurs when the print peels

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

off the table or the filament begins to accumulate in an uncontrolled manner. This makes it possible to quickly notice the problem and react, which increases the safety of the printer and reduces material waste during long or more demanding prints.

Manufacturer	QiDi
Model	Q2 Combo
Working area	270 × 270 × 256 mm
Printer dimensions	402 × 438 × 494 mm
Weight	18.1 kg
Head temperature	up to 370°C
Work table temperature	up to 120°C
Nozzle diameter	0.4 mm (optional 0.2 / 0.6 / 0.8 mm)
Extruder	Direct Drive, hardened steel gears
Maximum head speed	600 mm/s
Maximum acceleration	up to 20000 mm/s ²
Supported filaments	PLA, ABS, ASA, PETG, TPU, PA, PC, carbon and glass fiber composites, and others
Filament diameter	1.75 mm
Multi-color printing	Compatible with QIDI Box
Camera	Up to 1080p, timelapse support
Filament sensors	Filament end sensor and tangling detection (with QIDI Box)
Power failure resume function	Yes
Connectivity	2.4 GHz Wi-Fi, Ethernet, USB
Memory	32 GB eMMC + USB 2.0 memory
Display	4.3" touchscreen (480 × 272)
Slicing software	QIDI Studio, OrcaSlicer, PrusaSlicer, and others
Supported file formats	STL, OBJ, 3MF, STEP, STP

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

Power supply 110V / 220-240V AC, 50/60 Hz

Rated power 350 W + 280 W (chamber heating)

Printer type: FDM , Gross weight: 31570, Net weight: 24500, Box length: 54,00, Box width: 51,00, Box height: 59,00, Information about data generation: <https://dataact.innpro.pl/QiDi/744581222924>, PPWR: <https://ppwr.innpro.pl/qidi>

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950