



InLine 76660I interface cards/adapters Internal USB Type-C



Model: 76660I

Manufacturer: INLINE

EAN: 4043718341504

Product Code: 1292363

R1,761

Connection: 1x USB-C socket

Specification: USB 3.2 Gen.2x2 with up to 20 Gb/s

PCIe 3.0 x4 interface- compatible with x4, x8 and x16 slots

ASMedia ASM3242 chipset for high performance and stability

Supports UASP (USB Attached SCSI Protocol) for optimized data transfer

Plug & Play functionality- no driver required

The **InLine® PCIe interface card** adds a **high-performance USB-C port** with support for the **USB 3.2 Gen.2x2 standard** to your PC. This enables **extremely fast data transfer rates of up to 20 Gb/s**- ideal for **NVMe SSDs, external storage solutions and high-performance peripherals**. Thanks to the **PCIe 3.0 x4 connection**, the card offers high bandwidth and is compatible with **x4, x8 and x16 slots**. With **Plug & Play functionality, modern UASP support and optimized**

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

bandwidth management, it is a powerful addition to any system.

Technical data:

Bus type & PCIe: PCIe v3.0 (8 GT/s) x4 lane (compatible with x4, x8, x16 slots)

Chip set: ASMedia ASM3242

Power supply via USB-C: Up to 5 V/3 A

Form factor: Low profile

Dimensions: 79 mm x 51 mm (PCIe board)

Supported USB speeds:

SuperSpeed USB: 20 Gb/s, 10 Gb/s, 5 Gb/s

HiSpeed USB: 480 Mb/s

Features:

Plug & Play - no additional drivers required

Supports UASP (USB Attached SCSI Protocol) for optimized data transfer

Overcurrent protection for enhanced security

Optimized bandwidth by supporting multiple INs - ensures a stable and efficient connection

Backwards compatible with older USB standards

Operating system support:

Windows: 11, 10, 8, 7

Windows Server: 2008 R2, 2016, 2019, 2021

Linux: from kernel version 2.6.30

macOS: 10.8 and newer

Environmental conditions:

Operating temperature: 0 °C to 85 °C

Storage temperature: -25 °C to 85 °C

Maximum humidity: 90 %

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

Scope of delivery:

1x InLine® interface card, PCIe x4, 1x USB-C, USB 3.2 Gen.2x2

1x low-profile slot bracket

1x instruction manual (German/English)

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950