

PC Power Supply DEEPCOOL PF550X-FE, Black



Model: R-PF550X-HD0B-JGEU

Manufacturer: DEEPCOOL

EAN: 6933412756132

Product Code: 1296334

R1,409

Certification: CE/FCC/CCC/RCM/EAC/CAN ICES-003(B)/NMB-003(B) /TUV-RH | Compliance certificates: RoHS | Compliance certificates: CE | Compliance certificates: Federal Communications Commission (FCC) | Compliance certificates: BIS | Compliance certificates: UKCA | Product colour: Black | AC input frequency: 50/60 Hz | Operating temperature (T-T): 0 - -40 °C | AC input voltage: 100 - 240 V | Package type: Box | Input current: 8 A | Sustainability compliance: Yes | Power protection features: SCP (short circuit protection) | Fan diameter: 12 cm | Power Good signal delay range: 100 - 150 ms | Power protection features: OVP (overvoltage protection) | Power protection features: OCP (overcurrent protection) | Max output current (+12V): 62.5 A | Number of fans: 1 fan(s) | ATX version: 2.4 | Depth: 140 mm | Height: 86 mm | Power Factor Correction (PFC) type: Active | Power protection features: OPP (overload protection) | Power protection features: SIP (surge and shock protection) | Total power: 550 W | Fan location: Lower | Power protection features: UVP (undervoltage protection) | Motherboard power connector: 20+4 pin ATX | On/off switch: Yes |

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

Bearing technology: Hypro Bearing | Purpose: PC | Width: 150 mm | Cabling type: Non-Modular | Power supply unit (PSU) form factor: ATX | CPU power connector (4+4 pin): Yes | Peripheral (Molex) power connectors (4-pin): 2 | Number of SATA power connectors: 6 | ATX power connector (20+4 pin): Yes | Efficiency: 85% | 80 PLUS certification: 80 PLUS Bronze | Mean time between failures (MTBF): 1000000 h | Cooling type: Active | PCI Express power connectors (6+2 pin): 2 | Motherboard power cable length: 50 cm | Combined power (+12V): 550 W

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950