

PC Power Supply DEEPCOOL PF650X, Black



Model: R-PF650X-HD0B-JGEU

Manufacturer: DEEPCOOL

EAN: 6933412756279

Product Code: 1296335

R1,487

Certification: CE/FCC/CCC/RCM/EAC/CAN ICES-003(B)/NMB-003(B) /TUV-RH | Compliance certificates: Federal Communications Commission (FCC) | Compliance certificates: RoHS | Compliance certificates: CE | Compliance certificates: UKCA | Power protection features: UVP (undervoltage protection) | Power protection features: OCP (overcurrent protection) | Power protection features: OVP (overvoltage protection) | Sustainability compliance: Yes | Power protection features: OPP (overload protection) | Power protection features: SIP (surge and shock protection) | Power protection features: SCP (short circuit protection) | Combined power (+12V): 750 W | CPU power connector (4+4 pin): Yes | PCI Express power connectors (6+2 pin): 2 | Fan location: Lower | Power Factor Correction (PFC) type: Active | Number of SATA power connectors: 6 | ATX power connector (20+4 pin): Yes | Motherboard power connector: 20+4 pin ATX | ATX version: 2.52 | Bearing technology: Hypro Bearing | Power Good signal delay range: 100 - 150 ms | Width: 150 mm | Product colour: Black | Depth: 140 mm | Max output current (+12V): 54.2 A | AC input voltage: 100 - 240 V | Input current: 10 - 5 A | Peripheral (Molex) power connectors (4-pin): 2 | 80 PLUS certification: 80 PLUS Bronze | Number of fans: 1 fan(s) | Height: 86 mm | Cooling type: Active | AC input frequency:

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

50/60 Hz | On/off switch: Yes | Motherboard power cable length: 50 cm | Package type: Box |
Efficiency: 88% | Cabling type: Non-Modular | Total power: 650 W | Operating temperature (T-T): 0 - -
40 °C | Fan diameter: 12 cm | Power supply unit (PSU) form factor: ATX | Mean time between failures
(MTBF): 1000000 h | Purpose: PC

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950