



# CyberPower CP1200EIPFCRM2U uninterruptible power supply (UPS) Line- Interactive 1.2 kVA 720 W 8 AC outlet(s)

Model: CP1200EIPFCRM2U

Manufacturer: CYBERPOWER

EAN: 4711027798233

Product Code: 1300023

## R7,732

LED indicators: Yes | Cooling type: Active | Form factor: Rackmount | USB 2.0 ports quantity: 1 |  
Product colour: Black | Output power: 720 W | Operating temperature (T-T): 0 - 40 °C | Ethernet LAN  
(RJ-45) ports: 2 | Weight: 11.6 kg | AC outlets quantity: 8 AC outlet(s) | Operating relative humidity  
(H-H): 0 - 95% | Rack capacity: 2U | Power source type: AC | Compliance certificates: RoHS |  
Compliance certificates: CE | Depth: 274 mm | Housing material: Metal | Battery type: RBP0181 |  
Power protection features: Overload | Power protection features: Over voltage | EMI/RFI noise  
filtering: Yes | RS-232 ports: 1 | Battery technology: Sealed Lead Acid (VRLA) | Width: 433 mm |  
Typical backup time at half load: 11.6 min | Input frequency: 50/60 Hz | AC outlet types: C13 coupler

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices  
may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or  
typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

| Power factor: 0.6 | Input operation voltage (max): 271 V | UPS topology: Line-Interactive | Power Factor Correction (PFC) type: Active | Height: 86 mm | Automatic Voltage Regulation (AVR): Yes | Hot-swap battery: Yes | Power plug: C14 coupler | Heat dissipation: 17.1 BTU/h | Detachable power cord: Yes | Output frequency regulation: 1 Hz | Surge protection: Yes | Serial ports quantity: 1 | Output frequency: 50/60 Hz | USB port: Yes | Serial interface type: RS-232 | Number of batteries supported: 1 | Typical backup time at full load: 3.4 min | Display type: LCD | Input operation voltage (min): 169 V | ECO mode: Yes | Output power capacity: 1.2 kVA | Serial interface: Yes | Waveform: Pure sine | Built-in fan: Yes | Control type: Buttons | USB port type: USB Type-B

---

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

[itworkup.co.za](http://itworkup.co.za) | [sales@itworkup.co.za](mailto:sales@itworkup.co.za) | +27 (11)541-9950