

TP-Link 4G+ AX1800 Whole Home Mesh WiFi 6 Gateway



Model: DECO X20-4G

Manufacturer: TP-LINK

EAN: 6935364006709

Product Code: 1300424

R4,226

Supported WAN type: Dynamic IP/Static IP/PPPoE/L2TP/PPTP | Certification: CE, RoHS | Mobile network generation: 3G, 4G | UMTS bands supported: 2100 MHz | UMTS bands supported: 850 | UMTS bands supported: 900 | 3G standards: DC-HSPA+ | 4G bands supported: 2600 | 4G bands supported: 850 | 4G bands supported: 2500 MHz | 4G bands supported: 700 | 4G bands supported: 2300 | 4G bands supported: 900 | 4G bands supported: 1800 | Supported network protocols (IPv6): Y | 4G bands supported: 2100 | 4G bands supported: 800 | Wi-Fi band: Dual-band (2.4 GHz / 5 GHz) | WLAN data transfer rate (first band): 574 Mbit/s | 3G standards: UMTS | 3G standards: HSPA | Static IP: Yes | AC adapter input current: 0.6 A | 4G standard: TD-LTE & FDD-LTE | Dynamic DNS (DDNS): Yes | WLAN data transfer rate (second band): 1201 Mbit/s | Dynamic IP: Yes | Built-in processor: Yes | Port forwarding: Yes | Transmit power: CE: ≤20 dBm (2.4GHz), ≤23 dBm (5GHz) | Operating modes: 3G/4G, Router, Access Point | Number of devices supported: 150 | Ethernet cable: Yes | SIM card type: NanoSIM | Guest access: Yes | Harmonized System (HS) code: 85171800 | Number of guest networks (5 GHz): 1 | Point-to-point protocol over Ethernet (PPPoE): Yes | Number of guest networks (2.4 GHz): 1 | MU-MIMO technology: Yes | Cloud services supported: TP-Link ID | Reset button: Yes |

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

Warnings: Avoid contact with liquids as this may cause electric shock. | Package depth: 213.5 mm | MIMO: Yes | Quality of Service (QoS) support: Yes | Processor cores: 4 | Top Wi-Fi standard: Wi-Fi 6 (802.11ax) | AC adapter output voltage: 12 V | Product colour: White | AC adapter included: Yes | Storage temperature (T-T): -40 - 60 °C | Package height: 124 mm | Depth: 105 mm | Networking standards: IEEE 802.11ax | Height: 167 mm | Security algorithms: WPA-PSK | Wi-Fi standards: Wi-Fi 5 (802.11ac) | Antennas quantity: 4 | Wi-Fi standards: 802.11a | Wi-Fi standards: Wi-Fi 6 (802.11ax) | Wi-Fi standards: Wi-Fi 4 (802.11n) | DC-in jack: Yes | Package width: 241 mm | Ethernet WAN: Yes | Antenna type: Internal | Networking standards: IEEE 802.11b | Networking standards: IEEE 802.11g | Networking standards: IEEE 802.11n | Package weight: 1.22 kg | Width: 105 mm | Number of units included: 1 pc(s) | Warnings: Do not open the appliance housing - risk of electric shock. | Wi-Fi standards: 802.11g | Warnings: The product may emit radio waves that may interfere with other electronic devices. | Wi-Fi standards: 802.11b | Operating relative humidity (H-H): 10 - 90% | Ethernet LAN (RJ-45) ports: 3 | Operating temperature (T-T): 0 - 40 °C | Networking standards: IEEE 802.11ac | Number of products included: 1 pc(s) | Networking standards: IEEE 802.11a | AC input frequency: 50/60 Hz | AC adapter output current: 1.5 A | Security algorithms: WPA | Security algorithms: WPA3 | LED indicators: Power | Processor frequency: 1.5 GHz | AC input voltage: 100 - 240 V | Storage relative humidity (H-H): 5 - 90%

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950