

Thermaltake Smart RGB power supply unit 700 W 20+4 pin ATX ATX Black



Model: PS-SPR-0700NHSWE-1

Manufacturer: THERMALTAKE

EAN: 4711246870475

Product Code: 1304272

R2,025

Operating relative humidity (H-H): 20 - 85% | AC input frequency: 50 - 60 Hz | Power Factor Correction (PFC) type: Active | Safety: CE/CB/TUV/ EAC | Max output current (+12V): 54 A | Combined power (+3.3V): 120 W | Mean time between failures (MTBF): 100000 h | Max output current (-12V): 0.5 A | Operating temperature (T-T): 5 - 40 °C | Combined power (+12V): 648 W | Cabling type: Non-Modular | Total power: 700 W | Fan location: Top | Combined power (-12V): 6 W | Hold time: 16 ms | Product colour: Black | Storage relative humidity (H-H): 10 - 95% | Illumination: Yes | AC input voltage: 230 V | Input current: 9 A | Max output current (+5V): 17 A | 80 PLUS certification: 80 PLUS | Efficiency: 86% | Max output current (+3.3V): 24 A | Purpose: PC | Harmonized System (HS) code: 84733020 | Peripheral (Molex) power connectors (4-pin): 5 | Storage temperature (T-T): -40 - 55 °C | Noise level: 28.1 dB | Floppy disk drive connector: Yes | PCI Express power connectors (6+2 pin): 2 | Illumination colour: Multi | Combined power (+5Vsb): 12.5 W | Combined power (+5V): 120 W |

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

Motherboard power connector: 20+4 pin ATX | Max output current (+5Vsb): 2.5 A | ATX version: 2.3 |
Floppy drive power connector: 1 | Number of fans: 1 fan(s) | CPU power connector (4+4 pin): Yes |
Motherboard power cable length: 50 cm | CPU power cable length: 55 cm | ATX power connector
(20+4 pin): Yes | PCI Express connector: Yes | Fan diameter: 12 cm | Power supply unit (PSU) form
factor: ATX | Cooling type: Active | Package type: Box | Floppy disk drive cable length: 10 cm |
Number of SATA power connectors: 6 | Power Good signal delay range: 100 - 500 ms

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950