

Thermaltake Smart BX1 power supply unit 550 W 24- pin ATX ATX Black



Model: PS-SPD-0550NNSABE-1

Manufacturer: THERMALTAKE

EAN: 4711246875227

Product Code: 1304273

R1,603

Total power: 550 W | Fan location: Top | AC input voltage: 230 V | Cabling type: Non-Modular | AC input frequency: 50 Hz | Motherboard power connector: 24-pin ATX | ATX version: 2.3 | Combined power (-12V): 6 W | Operating temperature (T-T): 5 - 40 °C | Power Factor Correction (PFC) type: Active | Safety: CE, CB, TUV, EAC, RCM | Combined power (+3.3V): 105 W | SATA power cable length: 150 | Max output current (+3.3V): 21 A | Floppy disk drive connector: Yes | Width: 150 mm | Combined power (+5V): 105 W | Noise level: 37.6 dB | Cooling type: Active | Purpose: PC | Maximum input current (@220V): 10 A | SATA power cable length: 500 mm | Input current: 10 A | Depth: 140 mm | CPU power connector (4+4 pin): Yes | Efficiency: 88% | PCI Express connector: Yes | Number of fans: 1 fan(s) | Power Good signal delay range: 100 - 500 ms | Fan diameter: 12 cm | Height: 86 mm | Max output current (+12V): 38 A | PCI Express power connectors (6+2 pin): 2 | Peripheral (Molex) power connectors (4-pin): 4 | Storage relative humidity (H-H): 10 - 95% | Max output current (-12V):

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

0.5 A | Power supply unit (PSU) form factor: ATX | Motherboard power cable length: 60 cm | Peripheral (Molex) power cable length: 150 | Storage temperature (T-T): -40 - 55 °C | Peripheral (Molex) power cable length: 500 mm | 80 PLUS certification: 80 PLUS Bronze | Mean time between failures (MTBF): 100000 h | CPU power cable length: 65 cm | Operating relative humidity (H-H): 20 - 85% | Floppy drive power connector: 1 | Combined power (+5Vsb): 12.5 W | Number of SATA power connectors: 6 | Max output current (+5V): 16 A | Product colour: Black | Hold time: 16 ms | EPS version: 2.92 | Max output current (+5Vsb): 2.5 A | Peak power: 660 W | On/off switch: Yes | Illumination: No | Combined power (+12V): 456 W

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950