

Thermaltake Smart BX1 power supply unit 650 W 24- pin ATX ATX Black



Model: PS-SPD-0650NNSABE-1

Manufacturer: THERMALTAKE

EAN: 4711246875258

Product Code: 1304274

R1,745

Operating temperature (T-T): 5 - 40 °C | Storage temperature (T-T): -40 - 55 °C | PCI Express connector: Yes | Combined power (-12V): 6 W | Peripheral (Molex) power connectors (4-pin): 4 | On/off switch: Yes | AC input frequency: 50 - 60 Hz | Cabling type: Non-Modular | Total power: 650 W | Peak power: 80 W | Combined power (+5V): 110 W | EPS version: 2.92 | Product colour: Black | Depth: 140 mm | Number of fans: 1 fan(s) | Width: 150 mm | Operating relative humidity (H-H): 20 - 85% | CPU power connector (4+4 pin): Yes | ATX version: 2.3 | Combined power (+12V): 576 W | PCI Express power connectors (6+2 pin): 2 | SATA power cable length: 150 | Storage relative humidity (H-H): 10 - 95% | Max output current (+5Vsb): 2.5 A | CPU power cable length: 1 mm | Number of SATA power connectors: 6 | Purpose: PC | Max output current (+3.3V): 23 A | Cables included: CPU, PCIe, Peripheral (Molex), Peripheral (Molex) to SATA 3.3, SATA | Height: 86 mm | Peripheral (Molex) power cable length: 150 | Motherboard power cable length: 60 cm | Power Factor Correction (PFC)

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

type: Active | Max output current (+12V): 48 A | Peripheral (Molex) power cable length: 500 mm | Combined power (+3.3V): 110 W | Motherboard power connector: 24-pin ATX | Power supply unit (PSU) form factor: ATX | PCI Express power cable length: 50 cm | Input current: 12 A | Fan diameter: 12 cm | Cooling type: Active | SATA power cable length: 500 mm | Max output current (-12V): 0.5 A | Combined power (+5Vsb): 12.5 W | 80 PLUS certification: 80 PLUS Bronze | Mean time between failures (MTBF): 100000 h | AC input voltage: 100 - 240 V | Max output current (+5V): 17 A

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950