

Zebra DS3678-SR Handheld bar code reader 1D/2D LED Black, Green



Model: DS3678-SR3U42A0SFW

Manufacturer: ZEBRA

EAN:

Product Code: 1305697

R12,622

Battery capacity: 3100 mAh | International Protection (IP) code: IP67 | Sustainability certificates: RoHS | Power source type: Battery | Weight: 407 g | LED indicators: Yes | Protection features: Shock resistant | Protection features: Dust resistant | Linear (1D) barcodes supported: GS1-128 (UCC/EAN-128) | Linear (1D) barcodes supported: Plessey | Linear (1D) barcodes supported: Codabar | Protection features: Water resistant | Scanner type: 1D/2D | Depth: 76 mm | Bluetooth version: 4.0 | Linear (1D) barcodes supported: Code 128 | Linear (1D) barcodes supported: Code 39 | Connectivity technology: Wired & Wireless | Product colour: Black | Bluetooth Low Energy (BLE): Yes | Storage temperature (T-T): -40 - 70 °C | Tilt reading angle: -65 - 65° | Operating temperature (T-T): -20 - 50 °C | Harmonized System (HS) code: 84716070 | Standard interfaces: RS-232, USB, Keyboard wedge | Linear (1D) barcodes supported: Code 93 | Linear (1D) barcodes supported: U.P.C. | Width: 142 mm | Operating relative humidity (H-H): 5 - 95% | Programming function: Yes | Height: 185 mm | Product colour: Green | Linear (1D) barcodes supported: Code 11 | Linear (1D) barcodes supported: MSI |

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

Wavelength: 610 nm | Wireless range: 100 m | Yaw reading angle: -45 - 45° | Pitch reading angle: -65 - 65° | Ethernet LAN: Yes | Battery technology: Lithium-Ion (Li-Ion) | Sensor type: LED | 2D (matrix & stacked) barcodes supported: Data Matrix | 2D (matrix & stacked) barcodes supported: QR Code | 2D (matrix & stacked) barcodes supported: TLC-39 | 2D (matrix & stacked) barcodes supported: Composite Codes | 2D (matrix & stacked) barcodes supported: Micro QR Code | Optical sensor resolution: 1280 pixels | Type: Handheld bar code reader | 2D (matrix & stacked) barcodes supported: Han Xin | Number of reads per charge: 100000 | 2D (matrix & stacked) barcodes supported: PDF417 | 2D (matrix & stacked) barcodes supported: Aztec Code | 2D (matrix & stacked) barcodes supported: MicroPDF417 | 2D (matrix & stacked) barcodes supported: MaxiCode

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950