

Motorola LI4278 Black



Model: LI4278-TRBU0100ZER

Manufacturer: ZEBRA

Product Code: 1305698

R4,642

Decoding standards: UPC/EAN: UPC-A, UPC-E, UPC-E1, EAN-8/JAN 8, EAN-13/JAN 13, Bookland EAN, Bookland ISBN Format, UCC Coupon Extended Code, ISSN EAN Code 128 Including GS1-128, ISBT 128, ISBT Concatenation, Code 39 including Trioptic Code 39, Convert Code 39 to Code 32 (Italian Pharmacy Code), Code 39 Full ASCII Conversion Code 93 Code 11 Matrix 2 of 5 Interleaved 2 of 5 (ITF) Discrete 2 of 5 (DTF) Codabar (NW - 7) MSI Chinese 2 of 5 IATA Inverse 1D (except all GS1 DataBars) GS1 DataBar including GS1 DataBar-14, GS1 DataBar Limited, GS1 | Certification: EMC FCC Part 15 Class B, ICES 003 Class B, IEC 60601-1-2 RoHS 2002/95/EEC | Standard interfaces: RS-232, RS-485, USB, Keyboard wedge | Operating temperature (T-T): 0 - 50 °C | Weight: 224 g | International Protection (IP) code: IP54 | Tilt reading angle: 0 - 45° | Maximum scan width: 10 cm | Tilt angle range: 0 - 35° | Harmonized System (HS) code: 84716070 | Bluetooth: Yes | Yaw reading angle: 0 - 65° | Maximum range: 6 m | Shockproof: No | Wavelength: 612 nm | Product colour: Black | Operating relative humidity (H-H): 5 - 85% | Battery technology: Lithium Polymer (LiPo) | Light source: LED | Light levels (direct sunlight): 0 - 108 lx | LED indicators: Power | Cables included: RS-232 | Safety: C22.2 No. 60950-1, EN 60950-1, IEC 60950-1, UL 60950- 1 LED Class 1 | Read rate (max): 547 reads/s | Storage temperature (T-T): -40 - 70 °C | Pitch reading angle: 0 - 65° | LED indicators: Charging | Cable length: 1.8 m | Housing material: Plastic | Dimensions (WxDxH): 70 x 186 x 98 mm

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950