

NET POE+ ADAPTER 2.5G UNIFI/30W UACC-POE+- 2.5G UBIQUITI



Model: UACC-POE+-2.5G

Manufacturer: UBIQUITI

EAN: 810084699461

Product Code: 1306080

R978

An adapter that can power UniFi PoE+ devices, reduce dependency on PoE switch power, and provide a Multi-Gigabit LAN connection.

- Delivers up to 30W of PoE+
- Surge, peak pulse, and overcurrent protection
- Contains RJ45 data input, AC cable with earth ground, and PoE+ output
- LED indicator for status monitoring

Summary: Ubiquiti UACC-PoE+-2.5G. Ethernet interface type: 2.5 Gigabit Ethernet, Ethernet LAN data rates: 10,100,1000,2500 Mbit/s. Product colour: White, LED indicators: Status, Power protection features: Over current, Peak pulse, Surge protection. Power over Ethernet (PoE) voltage: 48 V, AC adapter input voltage: 100 - 240 V, AC adapter frequency: 50/60 Hz. Compliance certificates: CCC,

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

CE, Federal Communications Commission (FCC), Industry Canada (IC), KC, RoHS, UKCA, UL. Width: 62 mm, Depth: 35 mm, Height: 93 mm | Vendor Homepage: <https://eu.store.ui.com/eu/en/collections/pro-store-poe-and-power-adapters/products/uacc-poe-plus-2-5g> | Ethernet interface type: 2.5 Gigabit Ethernet | Ethernet LAN data rates: 10/100/1000/2500 | Power over Ethernet (PoE): Yes | Product colour: White | Wall mountable: Yes | Surge protection: Yes | LED indicators: Status | Power protection features: Over current/Peak pulse/Surge protection | Ethernet LAN (RJ-45) ports: 2 | Power over Ethernet (PoE) voltage: 48 | AC adapter input voltage: 100 - 240 | AC adapter frequency: 50/60 | Input current: 0.75 | Output current: 0.65 | Total Power over Ethernet (PoE) budget: 30 | Compliance certificates: CCC/CE/Federal Communications Commission (FCC)/Industry Canada (IC)/KC/RoHS/UKCA/UL | Operating temperature (T-T): 0 - 40 | Operating temperature (T-T): 32 - 104 | Operating relative humidity (H-H): 10 - 95 | Storage temperature (T-T): -30 - 70 | Width: 62 | Depth: 35 | Height: 93 | Weight: 156 | Number of products included: 1 | Unit Calculated Weight: 0.3775 | Product Net Weight: 0.156 | Units per Shipping Box: 40 | Unit Width: 11.2 | Unit Depth: 18.2 | Unit Height: 5.2 | Unit Calculated Volume: 0.0012904 | Shipping Box Height: 39.9 | Name: NET POE+ ADAPTER 2.5G UNIFI/30W UACC-POE+-2.5G UBIQUITI | Model: UACC-PoE+-2.5G | Model name: UACC-PoE+-2.5G

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950