

**Hikvision HM-
TD2628-
3/G1/T3A
security camera
Bullet IP
security camera
Outdoor 2688 x
1944 pixels Wall**



Model: HM-TD2628-3/G1/T3A

Manufacturer: HIKVISION

EAN: 6974004647766

Product Code: 1306218

R11,917

B/W night vision distance: 30 m | Audio formats supported: G.711 μ -law | Lens viewing angle, horizontal: 84° | Audio formats supported: MP2L2 | DC output current: 2.5 A | Web browser: Yes | Operating relative humidity (H-H): 0 - 95% | Zoom capability: Yes | Audio input: 3.5 mm | Alarm input channels: 2 | Power consumption (Power over Ethernet (PoE)): 24 W | Ethernet LAN (RJ-45) ports: 1 | Temperature measurement range: -20 - 150 °C | International Protection (IP) code: IP67 | LED type: IR/White | Dynamic range: 120 dB | Ethernet interface type: Fast Ethernet | Lens viewing angle, vertical: 43.1° | Number of simultaneous live view channels: 20 channels | IP address filtering: Yes | Mounting type: Wall | Number of detectable fire points: 10 | Output impedance: 600 Ω | Weight: 1.71

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices

may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or

typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

kg | Pixel pitch (thermal module): 12 µm | Recognize distance (wide): 37 m | Number of cameras: 1 | Alarm input/output: Yes | Horizontal field of view (thermal module): 50° | Power consumption (max): 24 W | Fixed focal length: 4.3 mm | User access level: Administrator, Operator, User | Operating temperature (T-T): -40 - 65 °C | Detect distance (tele): 460 m | Temperature measurement accuracy: 8 °C | Wi-Fi: No | Placement supported: Outdoor | Identify distance (tele): 56 m | Network access storage (NAS): Yes | Built-in HDD: No | Frame rate: 25 fps | Aperture number (thermal module): 1 | Length: 349.1 mm | Number of users: 32 user(s) | Audio formats supported: G.711 A-law | Audio formats supported: G.726 | Audio formats supported: PCM | Fire detection: Yes | Audio formats supported: G.722 | Connectivity technology: Wired | Minimum illumination: 0 lx | RS-485 ports: 1 | Progressive scan: Yes | Form factor: Bullet | Alarm output channels: 2 | Number of languages: 32 | Supported graphics resolutions: 1920 x 1080 (HD 1080) | Supported graphics resolutions: 1280 x 720 (HD 720) | Sensor type (thermal module): Vanadium Oxide Uncooled Focal Plane Arrays | Web-based management: Yes | Identify distance (wide): 15 m | Temperature sensor: Yes | Closest focusing distance: 0.3 m | Type: IP security camera | Languages support: Multi | Camera shutter speed: 1 - 1/100000 s | Maximum resolution: 2688 x 1944 pixels | Thermal sensitivity (NETD): 25 mK | DC output voltage: 12, 24, 42.5, 57 | Thermal module: Yes | HTTPS encryption: Yes | Supported graphics resolutions: 342 x 240 | Supported graphics resolutions: 704 x 480 | Supported graphics resolutions: 2688 x 1520 | Effective sensor resolution (thermal module): 256 x 192 pixels | Automatic Network Replenishment (ANR): Yes | Supported graphics resolutions: 352 x 288 | Night vision distance: 30 m | Vertical field of view (thermal module): 37.3° | Live view: Yes | Infrared spectral band: 8 - 14 µm | Supported graphics resolutions: 704 x 576 | Total megapixels: 5 MP | Supported graphics resolutions: 640 x 512 | Width: 113 mm | Night vision: Yes | Terminal block port: Yes | Supported network protocols: IPv4/IPv6,HTTP,HTTPS,802.1x,Qos,FTP,SMTP,UPnP,SNMP,DNS,DDNS,NTP,RTSP,RTCP,RTP,TCP,UDP,IGMP,ICMP,DHCP,PPPoE,Bonjour,SFTP,SRTP | Ethernet LAN: Yes | Compliance certificates: Low Voltage Directive (LVD) | Compliance certificates: Electromagnetic Compatibility (EMC) | Power source type: DC, PoE | Detect distance (wide): 150 m | Fixed focal length (thermal module): 3.6 mm | Height: 105 mm | Product colour: Black | Sensor type: CMOS | Quality of Service (QoS) support: Yes | Digital zoom: 4x | Maximum aperture number: 1.6 | Wide Dynamic Range (WDR): Yes | Compliance certificates: RoHS | Compliance certificates: CE | Compatible memory cards: MicroSDXC | Compliance certificates: REACH | Audio input channels: 1.0 channels | Compliance certificates: KC | Compliance certificates: WEEE | Compliance certificates: RCM | Compliance certificates: BIS | Product colour: White | Compatible memory cards: MicroSD (TransFlash) | Compatible memory cards: MicroSDHC | Compliance certificates: CB | Card reader

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

integrated: Yes | IK code: IK10 | Video compression formats: H.264 | Bluetooth: No | Video compression formats: M-JPEG | Password protection: Yes | Day/night mode: Yes | IFOV (spatial resolution): 3.33 mRad | Video compression formats: H.265 | Maximum memory card size: 512 GB | Recognize distance (tele): 112 m

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950