

**Zyxel GS1350-
6HP-EU0101F
network switch
Managed L2
Gigabit Ethernet
(10/100/1000)
Power over
Ethernet (PoE)
Grey**



Model: GS1350-6HP-EU0101F

Manufacturer: ZYXEL

EAN: 4718937604487

Product Code: 1314425

R3,923

Switching capacity: 12 Gbit/s | Product colour: Grey | Number of VLANs: 256 | Weight: 410 g | Power over Ethernet (PoE): Yes | Harmonized System (HS) code: 85176990 | Width: 193 mm | 10G support: No | Power consumption (max): 72 W | IGMP snooping: Yes | Copper ethernet cabling technology: 1000BASE-T | Copper ethernet cabling technology: 10BASE-T | Depth: 84 mm | Multicast support: Yes | Wall mountable: Yes | Heat dissipation: 245.52 BTU/h | Operating temperature (T-T): -20 - 50 °C | Copper ethernet cabling technology: 100BASE-TX | Storage temperature (T-T): -40 - 70 °C | Basic

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

switching RJ-45 Ethernet ports quantity: 5 | Security algorithms: SSH | Total Power over Ethernet (PoE) budget: 60 W | LED indicators: Yes | Mean time between failures (MTBF): 2021885.87 h | MAC address table: 8000 entries | VLAN support: Yes | Networking standards: IEEE 802.1ab | Security algorithms: SSL/TLS | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Networking standards: IEEE 802.1Q | Networking standards: IEEE 802.3x | Networking standards: IEEE 802.3bt | Web-based management: Yes | MAC address filtering: Yes | Networking standards: IEEE 802.3 | Networking standards: IEEE 802.3ab | Networking standards: IEEE 802.1p | Networking standards: IEEE 802.3ad | Security algorithms: SNMP | Operating relative humidity (H-H): 5 - 95% | Packet buffer memory: 0.525 MB | Power supply included: Yes | Networking standards: IEEE 802.3af | Networking standards: IEEE 802.3az | Networking standards: IEEE 802.3at | Networking standards: IEEE 802.1D | Networking standards: IEEE 802.3z | Storage relative humidity (H-H): 5 - 95% | Port mirroring: Yes | Networking standards: IEEE 802.1w | Firmware upgradeable: Yes | SFP module slots quantity: 1 | DHCP features: DHCP client | DHCP features: DHCP relay | Power over Ethernet (PoE) ports quantity: 5 | Height: 26 mm | DHCP features: DHCP snooping | Networking standards: IEEE 802.3u | Security algorithms: SNMPv3 | Warnings: Make sure the ventilation of the equipment is not blocked. | Warnings: Follow the safety guidelines for electrical current. | Warnings: Avoid contact of the device with liquid. | Virtual LAN features: Port-based VLAN | Configuring Location Settings (CLI): Yes | Flow control support: Yes | Queue scheduling algorithms: SPQ | Queue scheduling algorithms: Weighted Round Robin (WRR) | Rate limiting: Yes | Virtual LAN features: MAC address-based VLAN | System event log: Yes | Forwarding rate: 8.9 Mpps | IGMP proxy: Yes | Switch type: Managed | Fiber ethernet cabling technology: 1000BASE-X | Switch layer: L2 | Loop protection: Yes | Queue scheduling algorithms: WFQ | DC input voltage: 52 - 57 V | Spanning tree protocol: Yes | Broadcast storm control: Yes

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950