

GIGABYTE P550SS power supply unit 550 W 20+4 pin ATX ATX Black



Model: GP-P550SS

Manufacturer: GIGABYTE

EAN: 4719331554187

Product Code: 1314438

R1,464

ATX power connector (20+4 pin): Yes | CPU power cable length: 60 cm | CPU power connector (4+4 pin): Yes | PCI Express connector: Yes | Floppy drive power connector: 1 | Peripheral (Molex) power cable length: 500 mm | Max output current (+5Vsb): 3 A | Max output current (-12V): 0.3 A | PCI Express power cable length: 50 cm | Number of SATA power connectors: 5 | Motherboard power connector: 20+4 pin ATX | AC input voltage: 155-240 V | Depth: 140 mm | Power protection features: Over power | Power factor: 0.9 | Combined power (-12V): 3.6 W | Height: 86 mm | 80 PLUS certification: 80 PLUS Bronze | Mean time between failures (MTBF): 100000 h | Max output current (+5V): 20 A | Motherboard power cable length: 60 cm | Input current: 6.3 A | Efficiency: 90% | Power protection features: Overheating | Combined power (+5Vsb): 15 W | Cooling type: Active | Combined power (+3.3V): 100 W | Product colour: Black | On/off switch: Yes | Power supply unit (PSU) form factor: ATX | Hold time: 16 ms | Max output current (+12V): 45.8 A | Floppy disk drive connector: Yes | Fan location: Top | Total power: 550 W | SATA power cable length: 500 mm | Power protection

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

features: Short circuit | Power protection features: Over voltage | Power protection features: Under voltage | Power protection features: Over current | Purpose: PC | Cabling type: Non-Modular | Peripheral (Molex) power connectors (4-pin): 3 | PCI Express power connectors (6+2 pin): 2 | Combined power (+5V): 200 W | Max output current (+3.3V): 20 A | Harmonized System (HS) code: 84733020 | Power Factor Correction (PFC) type: Active | Width: 150 mm | AC input frequency: 50/60 Hz | Bearing technology: HDB | Combined power (+12V): 549.6 W | ATX version: 3.0 | Fan diameter: 12 cm | Number of fans: 1 fan(s)

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950