

Thermaltake TOUGHPower GF A3 power supply unit 1050 W 24-pin ATX ATX Black



Model: PS-TPD-1050FNFAGE-H

Manufacturer: THERMALTAKE

EAN: 4713227537612

Product Code: 1315472

R3,169

Certification: CE/FCC/UKCA/ICES/LVD/TUV/cTUVus/CB/CCC/BSMI | Floppy disk drive cable length: 15 cm | EPS power connector (4+4 pin): Yes | Product colour: Black | Height: 86 mm | ATX version: 3.0 | Floppy disk drive connector: Yes | Max output current (+3.3V): 20 A | Motherboard power cable length: 60 cm | Combined power (+3.3V): 100 W | Mean time between failures (MTBF): 100000 h | Fan diameter: 12 cm | Combined power (+5V): 100 W | 80 PLUS certification: 80 PLUS Gold | AC input voltage: 100 - 240 V | Motherboard power connector: 24-pin ATX | Cabling type: Fully-Modular | Storage relative humidity (H-H): 5 - 95% | Peripheral (Molex) power cable length: 800 | SATA power cable length: 800 | Peripheral (Molex) power cable length: 950 mm | Peripheral (Molex) power cable length: 650 | Max output current (+5V): 20 A | Combined power (+5Vsb): 15 W | Max output current (+12V): 87.5 A | Number of fans: 1 fan(s) | AC input frequency: 50/60 Hz | Operating relative humidity (H-H): 5 - 85% | Bearing technology: FDB | Input current: 16 A | Power supply unit (PSU)

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

form factor: ATX | Power Factor Correction (PFC) type: Active | PCI Express power connectors (6+2 pin): 5 | Max output current (+5Vsb): 3 A | Number of SATA power connectors: 12 | Peripheral (Molex) power cable length: 500 mm | Width: 150 mm | Storage temperature (T-T): -40 - 70 °C | PCI Express power connectors (12+4 pin): 1 | Total power: 1050 W | PCI Express power connectors (12+4 pin) cable length: 600 mm | Combined power (-12V): 3.6 W | Peripheral (Molex) power connectors (4-pin): 4 | Purpose: PC | SATA power cable length: 650 mm | SATA power cable length: 950 mm | Depth: 140 mm | SATA power cable length: 500 mm | Operating temperature (T-T): 0 - 45 °C | Combined power (+12V): 1050 W

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950