

NEEWER 6800 mAh, 14.5 V, 99 Wh Battery



Model: PS099E

Manufacturer: NEEWER

EAN: 6921268811471

Product Code: 1328430

R3,257

NEEWER PS099E 6800 mAh 14.5 V 99 Wh battery

The NEEWER PS099E is a compact V-Mount battery with a capacity of 6800 mAh (99 Wh) and a voltage of 14.54 V, providing stable and efficient power for professional photo and video equipment. With an output power of up to 65 W and support for PD fast charging, it works seamlessly with cameras, field monitors, and LED lights. Its compact dimensions of 111 × 73 × 56.7 mm and weight of 590 g make it easy to take on location without over-encumbering your gear.

Fast charging and high performance

The battery supports bidirectional PD fast charging up to 65 W and numerous protocols, such as PD 3.0, QC, and PPS, allowing for quick recharging and powering of various devices. A full charge takes about 3 hours using a compatible charger, and the large capacity ensures long runtime during video shoots and photo sessions. This solution helps minimize downtime and boost work efficiency on set.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

Versatile ports and broad compatibility

The PS099E model is equipped with multiple ports, including USB-A, USB-C, DC 8V and 12V, as well as BP and D-Tap connectors, enabling simultaneous power delivery to several devices. This allows you to connect a camera, monitor, and lighting without the need for additional adapters. The included port covers protect the connectors from dust and accidental damage.

Safety and convenience

The built-in battery management system (BMS) protects against overcharging, overheating, short circuits, and power surges, ensuring safe operation. The fire-resistant housing increases durability, and the easy-to-read OLED screen allows for a quick check of the charge status and real-time parameters. Additional non-slip elements improve grip and handling comfort while working in various conditions.

Included

- V-Mount PS099E Battery x1
- User Manual x1

Specifications

Manufacturer	Neower
Model	PS099E
Capacity	6800 mAh
Voltage	14.54 V
Energy	99 Wh
Input power	99 W
Output power	65 W
Charging time	Approx. 3 hours
USB-C input	20 V / 3.25 A
BP/D-Tap input	16.8 V / 8 A
USB-A output	5 V / 3 A, 9 V / 2 A, 12 V / 2 A

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

USB-C output Up to 20 V / 3.25 A

DC 8V output 8 V / 3 A

DC 12V output 12 V / 3 A

BP/D-Tap output 14.54 V / 14 A

Material V0 flame-retardant PC

Dimensions 111 × 73 × 56.7 mm

Weight 590 g

GPSR Link: <https://psr->

[assets.innpro.pl/photo_and_accessories/sg_photo_and_accessories_photo_accessories.pdf](https://psr-assets.innpro.pl/photo_and_accessories/sg_photo_and_accessories_photo_accessories.pdf), Gross weight: 890, Net weight: 567, Box length: 14,00, Box width: 10,00, Box height: 9,00

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950