

TP-Link 4G+ AX1800 Whole Home Mesh WiFi 6 Gateway



Model: DECO X20-4G

Manufacturer: TP-LINK

EAN: 6935364006709

Product Code: 1335497

R4,221

Supported WAN type: Dynamic IP/Static IP/PPPoE/L2TP/PPTP | Certification: CE, RoHS | Wi-Fi band: Dual-band (2.4 GHz / 5 GHz) | Ethernet cable: Yes | Harmonized System (HS) code: 85171800 | Built-in processor: Yes | Number of guest networks (2.4 GHz): 1 | UMTS bands supported: 2100 MHz | Static IP: Yes | 4G bands supported: 900 | UMTS bands supported: 900 | 4G bands supported: 2100 | 4G bands supported: 800 | Mobile network generation: 3G, 4G | 4G standard: TD-LTE & FDD-LTE | 4G bands supported: 2600 MHz | 4G bands supported: 850 | 4G bands supported: 2500 | 4G bands supported: 1800 | Supported network protocols (IPv6): Y | UMTS bands supported: 850 | 4G bands supported: 700 | 4G bands supported: 2300 | 3G standards: HSPA | 3G standards: UMTS | 3G standards: DC-HSPA+ | WLAN data transfer rate (second band): 1201 Mbit/s | Cloud services supported: TP-Link ID | Dynamic IP: Yes | Point-to-point protocol over Ethernet (PPPoE): Yes | Transmit power: CE: ≤20 dBm (2.4GHz), ≤23 dBm (5GHz) | Dynamic DNS (DDNS): Yes | Port forwarding: Yes | Number of devices supported: 150 | AC adapter input current: 0.6 A | Number of guest networks (5 GHz): 1 | MU-MIMO technology: Yes | SIM card type: NanoSIM | Guest access: Yes | WLAN data transfer rate (first band): 574 Mbit/s | Operating modes: 3G/4G, Router, Access Point |

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

MIMO: Yes | Quality of Service (QoS) support: Yes | Package depth: 213.5 mm | Height: 167 mm | Depth: 105 mm | Operating temperature (T-T): 0 - 40 °C | Product colour: White | AC adapter included: Yes | Storage temperature (T-T): -40 - 60 °C | AC adapter output voltage: 12 V | Package weight: 1.22 kg | AC adapter output current: 1.5 A | Package height: 124 mm | Number of products included: 1 pc(s) | Ethernet LAN (RJ-45) ports: 3 | Wi-Fi standards: 802.11b | AC input voltage: 100 - 240 V | Warnings: Do not open the appliance housing - risk of electric shock. | Width: 105 mm | Warnings: Avoid contact with liquids as this may cause electric shock. | LED indicators: Power | Processor frequency: 1.5 GHz | Antennas quantity: 4 | Antenna type: Internal | Processor cores: 4 | Top Wi-Fi standard: Wi-Fi 6 (802.11ax) | Warnings: The product may emit radio waves that may interfere with other electronic devices. | Package width: 241 mm | Security algorithms: WPA-PSK | Security algorithms: WPA3 | Reset button: Yes | Wi-Fi standards: 802.11g | Networking standards: IEEE 802.11g | Networking standards: IEEE 802.11n | Wi-Fi standards: Wi-Fi 4 (802.11n) | Networking standards: IEEE 802.11ac | Networking standards: IEEE 802.11a | Wi-Fi standards: 802.11a | Wi-Fi standards: Wi-Fi 6 (802.11ax) | Number of units included: 1 pc(s) | Networking standards: IEEE 802.11ax | Security algorithms: WPA | Networking standards: IEEE 802.11b | Wi-Fi standards: Wi-Fi 5 (802.11ac) | AC input frequency: 50/60 Hz | DC-in jack: Yes | Operating relative humidity (H-H): 10 - 90% | Ethernet WAN: Yes | Storage relative humidity (H-H): 5 - 90%

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950