



InLine 17990T HDMI cable 90 m HDMI Type A (Standard) Black



Model: 17990T

Manufacturer: INLINE

EAN: 4043718347308

Product Code: 1337168

R5,011

Seamless AV transmission over long distances:The HDMI AOC cable enables stable, high-resolution signal transmission up to 8K at 60 Hz and 4K at 120 Hz.

Reinforced and robust for continuous use:Metal armor and protected connectors protect the cable against mechanical stress and external influences.

High flexibility without loss of performance:The integrated fiber optic technology ensures interference-free transmission without an additional power supply.

Practical handling thanks to cable reel:The integrated reel facilitates transport, storage, and controlled laying of the cable.

Safe under electromagnetic stress:The design is resistant to electromagnetic and high-frequency interference.

The InLine HDMI AOC cable reel is suitable for professional AV installations where signal quality, flexibility, and range are crucial. The cable transmits HDMI 2.1 signals in resolutions up to 8K at 60 Hz and 4K at 120 Hz. It achieves a bandwidth of 48 Gb/s and does not require an additional power

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

connection. The directional signal routing (source to display) ensures clear and reliable signal distribution.

Thanks to its metal-shielded design, the cable can withstand high tensile and compressive forces. The integrated connectors are secured by robust protective sleeves. This prevents damage during storage or use. The cable reel allows for easy unwinding and rewinding as well as secure storage. The cable is ideal for demanding environments such as trade shows, live events, conference rooms, or permanently installed AV systems. It provides an interference-free connection even with complex signal architectures.

HDMI Type A plug ↔ HDMI Type A plug

8K @ 60 Hz, 48 Gb/s, HDMI 2.1

Directional - Source → Display

Supports EDID, HDCP, CEC, eARC

Passive operation - no external power supply required

PVC jacket, cable color black

Ø 5.5 mm, cable length 50 m / 90 m

Operating temperature –20 °C to +50 °C

Storage temperature –20 °C to +70 °C