

TP-Link Archer 4G+ Cat6 AC1200 Wireless Dual Band Gigabit Router



Model: Archer MR505

Manufacturer: TP-LINK

EAN: 8885020620078

Product Code: 1337681

R2,803

Warnings: Do not expose the device to extreme temperatures. | Warnings: Do not dismantle the unit yourself, there is a risk of electric shock. | Warnings: Do not expose the device to water or moisture. | Quick start guide: Yes | DHCP client: Yes | Ethernet LAN data rates: 1000 Mbit/s | Ethernet LAN data rates: 10 | Security algorithms: WPA3 | Security algorithms: 64-bit WEP | Product colour: White | Security algorithms: WPA | Security algorithms: 128-bit WEP | Ethernet LAN data rates: 100 | DC-in jack: Yes | Operating temperature (T-T): 0 - 40 °C | Wi-Fi band: Dual-band (2.4 GHz / 5 GHz) | 3G standards: HSPA+ | Ethernet LAN (RJ-45) ports: 3 | 4G standard: LTE-TDD & LTE-FDD | Package type: Box | Ethernet LAN interface type: Gigabit Ethernet | Dynamic DNS (DDNS): Yes | 3G standards: DC-HSPA+ | 3G standards: UMTS | Output current: 1.5 A | Power source type: DC | Product type: Desktop/pole router | Height: 57 mm | WLAN data transfer rate (max): 1200 Mbit/s | AC adapter included: Yes | 4G bands supported: 1800 | VPN server: Y | Wi-Fi standards: Wi-Fi 4 (802.11n) | 4G bands supported: 2600 MHz | 4G bands supported: 850 | 4G bands supported: 2500 | DHCP server:

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

Yes | 4G bands supported: 900 | Antenna design: Internal | Storage relative humidity (H-H): 5 - 90% | 4G bands supported: 700 | 4G bands supported: 2300 | WLAN data transfer rate (second band): 867 Mbit/s | Wi-Fi standards: 802.11a | Wi-Fi standards: 802.11g | Cabling technology: 10/100/1000Base-T(X) | Depth: 157.5 mm | SIM card slot: Yes | Mobile network generation: 4G | 4G bands supported: 2100 | 4G bands supported: 800 | Antennas quantity: 2 | Number of guest networks (2.4 GHz): 1 | Output voltage: 12 V | Width: 212 mm | Wi-Fi standards: Wi-Fi 5 (802.11ac) | Wi-Fi standards: 802.11b | Parental control: Yes | 3G bands supported: 2100 MHz | 3G bands supported: 850 | Number of guest networks (5 GHz): 1 | WLAN data transfer rate (first band): 300 Mbit/s | 3G bands supported: 900 | Ethernet LAN: Yes | Indication light: Yes | Detachable antenna(s): Yes | Static route: Yes | Operating relative humidity (H-H): 10 - 90% | Top Wi-Fi standard: Wi-Fi 5 (802.11ac) | Ethernet WAN: Yes | USB port: No

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950